NH fuse enclosure

# GST 4365-400



## GST 4365-400

**NH fuse enclosure**

CUSTOMIZABLE

Productnumber: 04646584
Dimensions: 640 x 320 x 179 mm

busbar enclosure, equipped with 6 x NH 000 fuse switch disconnector, Elevator clamp 1.5 - 50 mm², bottom side output, 5-pole busbar, with 5 busbar terminals for direct connection of a cable to the busbar system, additional N and PE terminal for each switch, 4 x enclosure connectors (GGV)

**busbar system 400 A, with transparent cover**

IP65 IK08 690V AC

Created at 04.06.2026. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

# Technical Data

## electrical characteristics

| | |
|---|---|
| Rated operating voltage AC: | 690 V |
| Protection class: | II |
| Type of protection: | IP65 |
| Rated current: | 400 A |
| UL Type Rating: | 3R |

## Dimensions

| | |
|---|---|
| Width: | 640 mm |
| Length: | 320 mm |
| Height: | 179 mm |
| Weight: | 13.9 kg |

## Material characteristics

| | |
|---|---|
| UV-resistant: | yes |
| Halogen free: | yes |
| Glow-wire flammability: | 960 °C (EN 60695-2-11) |

## mechanical properties

| | |
|---|---|
| Impact strength: | IK08 |
| Cover screw torque: | 2.5 Nm |

## Ambient conditions

| | |
|---|---|
| max. relative humidity 25°C: | 95 % |
| max. relative humidity 40°C: | 50 % |
| Min. ambient temperature: | -25 °C |
| Max. ambient temperature: | 40 °C |
| 24h ambient temperature: | 35 °C |
| Installation location: | protected outdoor areas |

## Sales Information

| | |
|---|---|
| EAN: | 4013902689460 |
| ETIM Class: | EC000249 |
| Custom tariff number: | 85369095 |
| Minimum order quantity: | 1 |

## Material

| | |
|---|---|
| Base unit material: | Polycarbonate |
| Cover material: | Polycarbonate, glass-fibre reinforced |
| Sealing material: | Polyurethane |
| Cover screw material: | Polyamide, glass-fibre reinforced |

## Accessories

07251401 - GFS 14-m - Flange set

07505601 - GSV 56 - Busbar connector