# 7516 VDE Kraftform Safe-Torque Speed Torque screwdriver, 2.4-4.0 Nm, 9 x 2.4 Nm x 2.8 Nm x 3.2 Nm x 3.6 Nm x 4.0 Nm x 192 mm




| | | | |
|---|---|---|---|
| **EAN:** | 4013288233585 | **Size:** | 199x66x36 mm |
| **Part number:** | 05075876001 | **Weight:** | 231 g |
| **Article number:** | 7516 VDE | **Country of origin:** | CZ |
| | | **Customs tariff number:** | 82041100 |

- VDE bladeholding torque screwdriver 7516 with 5 pre-set values (2.4; 2.8; 3.2; 3.6; 4.0 Nm)
- Speed: Extremely fast setting of desired torque values
- Safe: Slip-over torque function which can not be overtightened - for clockwise/counterclockwise torque operation
- Torque Lock function: for high tightening and loosening moments without torque
- With fast-rotating sleeve and mounting for Wera VDE interchangeable blades
- Accuracy ±10%

VDE-insulated torque wrench handle with 9 mm hexagon mounting; solely for Wera Kraftform Kompakt VDE blades. For professional screwdriving/fine adjustment AND for torque operated screwdriving. Slip-over torque function which can not be overtightened - for clockwise/counterclockwise torque operation. With five selectable tightening torques clockwise/counterclockwise (2.4; 2.8; 3.2; 3.6; 4.0 Nm), which can be set very quickly. Accuracy ±10%. One fixed position (Torque Lock) for unlimited loosening and tightening moments. With fast-rotating sleeve for easy wielding of the tool whilst screwdriving.

**Web link**
https://www.wera.de/en/05075876001

Wera - 7516 VDE
05075876001 - 4013288233585

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de



VDE bladeholding torque screwdriver 7516 with 5 pre-set values (2.4; 2.8; 3.2; 3.6; 4.0 Nm)

### Individually tested




The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.

### Handle for Wera VDE blades



The Safe-Torque Speed VDE bladeholding screwdriver is suitable solely for Wera VDE blades.

### Five selectable tightening torques




Five selectable tightening torques (2.4; 2.8; 3.2; 3.6; 4.0 Nm) and one fixed position (Torque Lock) for unlimited tightening and loosening moments.

### Quick torque setting




Quick setting of the selectable tightening torque values.

### Excess-load signal



Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

### Safe torque transfer




The slip-over torque mechanism for clockwise/counterclockwise torque operation prevents unintentional application of excessive torque.

### Further versions in this product family:

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| | mm | Nm | Nm | Nm | Nm | Nm | mm |
| 05075876001 | 9 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 192 |

**Web link**
https://www.wera.de/en/05075876001

Wera - 7516 VDE
05075876001 - 4013288233585

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de