Standard opening undervoltage release MN, ComPacT NS630b/NS3200, fixed, 100/130V AC/DC, spare part





Main

Range	ComPacT
Range of product	ComPacT NS630b1600 new generation ComPacT NS1600b3200 new generation
Device short name	MN
Product or component type	Voltage release
Device application	Control
Voltage release type	Opening coil Undervoltage release
Control type	Standard
[Uc] control circuit voltage	100130 V AC 50/60 Hz 100130 V DC
Circuit breaker mounting mode	Fixed
Range compatibility	ComPact ComPact NS630b1600 ComPact ComPact NS1600b3200

Complementary

Operating threshold	0.350.7 x Un opening 0.85 x Un closing
Response time	90 ms +/- 5 % for Compact NS630b1600 90 ms +/- 5 % for Compact NS1600b3200 40 ms +/- 5 % for MasterPact NT 90 ms +/- 5 % for MasterPact NW
Supply holding power	4.5 VA
Accessory / separate part category	Spare part for MasterPact NT Spare part for MasterPact NT NAVY Spare part for MasterPact NW Spare part for MasterPact NW NAVY Spare part for MasterPact NW NAVY Spare part for ComPacT NS630b1600 new generation Spare part for ComPacT NS1600b3200 new generation

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6.1 cm
Package 1 Length	8.3 cm
Package 1 Weight	153.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	13.0 cm
Package 2 Width	9.0 cm
Package 2 Length	18.0 cm
Package 2 Weight	1.576 kg
Unit Type of Package 3	S03
Number of Units in Package 3	40
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent or and is not to be used for determining suitability or inhability of these products for specific user applications. It is the dourn aren in integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 3 Length	40.0 cm
Package 3 Weight	6.791 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months
----------	-----------