

IE-FCI-PWCB-3A

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, Front-Com® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the Front-Com® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

General ordering data

Version	FrontCom, Fuse, Fuse insert
Order No.	1543690000
Type	IE-FCI-PWCB-3A
GTIN (EAN)	4050118348859
Qty.	1 items

Technical data

Approvals

Approvals



ROHS	Conform
UL File Number Search	UL Website
Certificate No. (UR)	E479289

Dimensions and weights

Net weight	37 g
------------	------

Temperatures

Storage temperature	Operating temperature
Installation temperature	

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	8bl
REACH SVHC	No SVHC above 0.1 wt%

General data

Product type	Fuse	Insert type	Fuse insert
--------------	------	-------------	-------------

General standards

Certificate No. (DNV)	TAA000022B	Certificate No. (UR)	E479289
-----------------------	------------	----------------------	---------

Technical data

Type of connection	Flat-blade receptacles 6.5 mm	Nominal current	3 A
Resistance	0,069 Ω typ.	Operating voltage	32 V DC, 250 V AC
Current-carrying capacity	1.5 kVeff		

Classifications

ETIM 8.0	EC001121	ETIM 9.0	EC001121
ETIM 10.0	EC001121	ECLASS 14.0	27-44-03-90
ECLASS 15.0	27-44-03-90		