# 1567 TORX® HF ESD Kraftform Micro screwdriver with holding function for TORX® screws, TX 5 x 40 mm




| | | | |
|---|---|---|---|
| **EAN:** | 4013288183989 | **Size:** | 157x13x13 mm |
| **Part number:** | 05030401001 | **Weight:** | 13 g |
| **Article number:** | 1567 TORX® HF ESD Micro | **Country of origin:** | CZ |
| | | **Customs tariff number:** | 82054000 |

- Kraftform Micro screwdriver for TORX® screws
- ESD-safe tool thanks to surface resistance of ≤ 10<sup>9</sup> Ohm
- Multi-component Kraftform Micro handle for fast and ergonomic screwdriving
- Holding function for TORX® screws
- Take it easy tool finder: colour coding according to profile and size
- The Wera Black Point tip offers an exact fit and optimum corrosion protection

ESD-safe Micro screwdriver. Dependable protection against electrostatic energy and associated damage. Holding function: the wedging forces resulting from the contact pressure between the drive tip and the screw profile securely hold the screw on the tool. Rapid twisting results from fixing the hand on the head and using the fast-turning zone just below. This makes time-consuming grip adjustments unnecessary. Power zones with integrated soft sections ensure the transfer of high loosening and tightening torque; a precision zone for the right rotation angle during fine adjustment work. The Black Point tip offers optimised corrosion protection and an exact fit. Take it easy tool finder with colour coding according to profiles and size stamp - for simple and rapid accessing of the required tool.




















**Web link**
https://www.wera.de/en/05030401001

Wera - 1567 TORX® HF ESD Micro
05030401001 - 4013288183989

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

### Wera ESD Tools




The requirements for ESD-safe screwdrivers are specified in the European standard DIN EN 61340-5-1. This standard also includes a handle that has to be out of a defined conductive material. The Wera products in the ESD series satisfy these standards and the even more stringent requirements demanded by some technology companies.

### High protection



The electric surface resistance of the Wera ESD material is ≤ 10<sup>9</sup> ohm. This securely protects components against electrostatic energy and associated damage.

### TORX® HF profile




In tight assembly or disassembly situations, for example in engine compartments, it is not possible to securely hold the screw with the hand on the screwdriver, and the screw subsequently often gets lost. Lengthy searches or the loss of the screw (with the associated danger that could bring about) are the consequence. The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that the screw is securely held on the tool!

### Kraftform Micro handle




Multi-component screwdriver handle for ergonomic working.

### The precision zone



The precision zone directly above the blade gives the user a better feel for the right rotation angle during fine adjustment work.

### The power zone




The power zone has integrated soft zones near the blade tip to ensure high torque transfer for loosening or tightening screws without losing contact with the screw.

### Rotating cap and fast-turning zone



The fast-turning zone just below the rotating cap allow rapid twisting. This makes time-consuming grip adjustments as with other conventional precision screwdrivers unnecessary.

### Wera Black Point tip



The Wera Black Point tip and a refined hardening process ensure long service life of the tip, improved corrosion protection and an exact fit.

**Web link**
https://www.wera.de/en/05030401001

Wera - 1567 TORX® HF ESD Micro
05030401001 - 4013288183989

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Further versions in this product family:

| | | mm | mm | mm | inch |
|---|---|---|---|---|---|
| 05030400001 | TX 4 | 40 | 97 | 2.5 | 1 9/16" |
| **05030401001** | **TX 5** | **40** | **97** | **3.0** | **1 9/16"** |
| 05030402001 | TX 6 | 40 | 97 | 3.0 | 1 9/16" |
| 05030403001 | TX 7 | 60 | 97 | 3.0 | 2 3/8" |
| 05030404001 | TX 8 | 60 | 97 | 3.0 | 2 3/8" |
| 05030405001 | TX 9 | 60 | 97 | 4.0 | 2 3/8" |
| 05030406001 | TX 10 | 60 | 97 | 4.0 | 2 3/8" |

Web link
https://www.wera.de/en/05030401001

Wera - 1567 TORX® HF ESD Micro
05030401001 - 4013288183989



Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de