



## Main

Product range	Thorsman
Range of product	Thorsman installation material
Product type	Cable tie
Colour	Clear
Quantity per package	Set of 100

## Complementary

Minimum tightening diameter	3.5 mm
Maximum tightening diameter	84 mm
Condition of use	Indoor
Resistance to tearing	Resistance to tearing: 180 N
Material	PA (polyamide) 6.6 UV-stabilised
Length	300 mm
Width	3.6 mm
Thickness	1.2 mm
Net weight	0.131 kg
Market segment	Small commercial

## Environment

Environmental characteristic	Fire resistance needle flame 30 s conforming to IEC 60695-11-5
Flame retardance	Self-extinguishing conforming to UL 94 V2
Ambient air temperature for operation	-40...85 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.500 cm
Package 1 Width	10.000 cm
Package 1 Length	32.000 cm
Package 1 Weight	138.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	60
Package 2 Height	15.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	9.018 kg
Unit Type of Package 3	P12
Number of Units in Package 3	1200
Package 3 Height	105.000 cm

Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	198.500 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations