



Hoofd

Range	Thorsman
Range of product	Thorsman installation material
Product or component type	Kabelbinder
Kleurtint	Helder
Quantity per set	Set van 100

Complementair

Minimum tightening diameter	3,5 mm
Maximale aanspandiameter	84 mm
Gebruiksvoorwaarde	Binnen
Mechanische stevigheid	Resistance to tearing: 180 N
Materiaal	PA (polyamide) 6.6 UV-stabilised
Lengte	300 mm
Width	3,6 mm
Dikte	1,2 mm
Net weight	0,131 kg
Market segment	Klein commercieel

Omgeving

Milieu-eigenschappen	Vuurbestendigheid needle flame 30 s conform aan IEC 60695-11-5
Vlamvertraging	Zelf dovend conform aan UL 94 V2
Ambient air temperature for operation	-40...85 °C

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2,500 cm
Package 1 Width	10,000 cm
Package 1 Length	32,000 cm
Package 1 Weight	138,000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	60
Package 2 Height	15,000 cm
Package 2 Width	40,000 cm
Package 2 Length	60,000 cm
Package 2 Weight	9,018 kg
Unit Type of Package 3	P12
Number of Units in Package 3	1200
Package 3 Height	105,000 cm

Package 3 Width	80,000 cm
Package 3 Length	120,000 cm
Package 3 Weight	198,500 kg

Duurzaamheid van het aanbod

Duurzaamheids status van het aanbod	Green Premium product
REACH-regelgeving	 REACH-verklaring
REACH vrij van SVHC	Ja
EU-richtlijn RoHS	Voldoet pro-actief (Product valt niet onder de EU RoHS juridische scope)  EU-verklaring RoHS
RoHS-regulering China	 RoHS-verklaring China
Informatie over RoHS-vrijstelling	 Ja
Milieu Profiel	 Milieuprofiel Van Het Product
Circulair Profiel	Geen specifieke recycling vereist