KYRO+1 SR/150

Part number 306604



Description

Series of LED street lighting luminaires, ,comprising:
- Die-cast aluminium housing and cover, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Polyester powder coat finish die-cast aluminium pole clamp
- Extra clear, toughened, flat glass diffuser
- High-transparency polycarbonate optics
- StReet optic options: SR/075 usually for narrow roads (0.5 ≥ L/H ≥ 0.75), SR/100 for two-lane roads (L/H = 1), SR/125 for wide streets and (L/H = 1.25), SR/150 for wide roads/parking lots (L/H = 1.5) schemes. L/H ratio (L-road width/H-pole height)
- Aluminium heat sink
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- The integral switch splitter automatically disconnects the driver from mains when opened
- Anti-tear cable gland M25x1.5 for cables Ø 9 - Ø 14 mm
- Built-in driver
- Stainless steel locking hardware
- Fibreglass technopolymer components plate holder
- Toolless removable and upgradable gear tray
- Fully integrated stainless steel aluminium spring clips
- Suitable for pole installations Ø 42 - Ø 60/62 mm (KYRO+ 1 models), Ø 76 mm (KYRO+ 1-D76), and Ø 60/62 - Ø 76 mm (KYRO+ 2)
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- The Secure Light Distribution (SLD) system guarantees uniform light distribution even in the remote case of LED failures
- UNI 10819 light pollution standards compliant (0% ULOR rating)
- Provided complete with 1 m cable H07RN-F 2 x 1.5 mm^2 and IP66-rated plug-socket, produced in polyamide with silver-plated brass contacts, for cables Ø 9 - Ø14 mm, for mains connection without opening the luminaire
- Automatic power reduction (RPA) options available. Consult factory
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- CLO (Constant Light Output) options available. Consult factory
- Design by SILVIA PAOLA PENNACCHIO

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

- Design by SILVIA PAOLA PENNACCHIO

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Product data

ETIM Group:	EG000027	**ETIM Class:**	EC000062

General information

Lampholder:	LED	**Light source:**	LED
Lightsource lumen output [lm]:	5431	**Luminaire lumen output [lm]:**	4898
Luminaire wattage [W]:	36 W	**Luminous efficacy [lm/W]:**	136
CRI:	70	**Colour temperature [K]:**	4000
Colour / Finishing:	AN-96 / Anthracite gray / Textured	**IP degree of protection:**	IP66
Impact resistance / impact energy:	IK09 10J xx9	**Protection class:**	II
Optic:	SR/150 - Street	**Net weight [kg]:**	6.95
Overall length [mm]:	275	**Overall width [mm]:**	690
Overall height [mm]:	131		

Mechanical features

Shape:	Rectangular	**Housing material:**	Aluminium
Diffuser material:	Glass	**Glow wire test [°C]:**	850 °C
Lateral exposed area [m²]:	0.07	**Top exposed area [m²]:**	0.17

Electrical features

Voltage type:	AC	**Input voltage [V AC]:**	220/240
Input frequency [Hz]:	50/60	**Power factor / COS Φ:**	>0.9
Surge protection | Common [kV]:	6.000000	**Surge protection | Differential [kV]:**	10.000000
Inrush current [A/µs]:	40 / 300	**C10 1.5 mm²:**	16
C16 2.5 mm²:	26	**B10 1.5 mm²:**	8
B16 2.5 mm²:	14		

Installation

Application area:	Outdoor lighting	**Mounting type:**	Streetlight
Min. ambient temperature [°C]:	-40	**Max. ambient temperature [°C]:**	50
Min. distance from lighted object [m]:	0.50		

Light features

MacAdam:	3	**Lumen maintenance:**	L90B10@100000h
Distribution of light emission:	Direct	**Luminous Intensity Class:**	G*4
Zero light pollution (ULR = 0%):		**IPEA* (road lighting):**	A7+
IPEA* (large areas, roundabouts):	A8+	**IPEA* (cycle-pedestrian):**	A7+
IPEA* (green areas):	A7+	**IPEA* (historic city centers):**	A11+

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Photometric data



Optional accessories

KYRO+

14077820

Kit of 10 rubber sealing gaskets for up to 2 no. Ø 8 mm cables

3102824

1 m Wire H07RN-F 2x1,5 + connector



14077102

Single 1200 mm extension arms, hot dipped galvanised steel, suitable for installation on Ø 60 mm pole top



14081902

Hot dipped galvanised steel brackets suitable for installing single fittings (back to Back) on Ø80-120mm poles. Complete with fixing rods and nuts, requires poles to be drilled



14084202

Hot dipped galvanised steel brackets suitable for installing single or twin fittings (back to Back) on Ø80-120mm poles. Complete with fixing rods and nuts, requires poles to be drilled

KYRO+ SOLUTION / KYRO+1

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

date: 22/10/2026



14077596

Wall mounting bracket L=310 mm (KYRO+1), in phospho-chromate and cataphoresispre-treated steel finished polyester painted

AN-96 / Anthracite gray

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com