


Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com





The unique modular concept can be tailored to every type of machine. The potential distribution terminal blocks AAP are successful thanks to their uniform design with two possible constructions – alternating or grouped. In the grouped structure of the control voltage distribution, the potentials are located on different terminal blocks and thus form entire potential blocks.

Version	Supply terminal, PUSH IN, 10 mm², 800 V, 57 A, beige, dark beige
Order No.	<u>2683450000</u>
Туре	AAP12 10 LO WT
GTIN (EAN)	4064675049135
Qty.	20 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

-			
Dim	ensions	and	weights

Depth	53.5 mm	Depth (inches)	2.106 inch
Height	85.5 mm	Height (inches)	3.366 inch
Width	10 mm	Width (inches)	0.394 inch
Net weight	27.05 g		

Temperatures

Storage temperature	-25 °C55 °C	Continuous operating temp., min.	-60 °C	
Continuous operating temp., max.	130 °C			

Material data

Material	Wemid	Colour	beige, dark beige
Colour of operational elements	white	UL 94 flammability rating	V-0

Rating data IECEx/ATEX

Certificate No. (ATEX)	TUEV17ATEX8030U	Certificate No. (IECEX)	IECEXTUR17.0015U
Max. voltage (ATEX)	690 V	Current (ATEX)	45 A
Wire cross section max. (ATEX)	10 mm²	Max. voltage (IECEX)	690 V
Current (IECEX)	45 A	Wire cross section max. (IECEX)	10 mm²
Marking EN 60079-7	Ex ec II C Gc	Ex 2014/34/EU label	II 2 G D

System specifications

End cover plate required	Yes	Number of potentials	1
Number of levels	1	Number of clamping points per level	1
Levels cross-connected internally	No	PE connection	No
Rail	TS 35	PE function	No

Additional technical data

Explosion-tested version	Yes	Type of mounting	Snap-on, TS 35

Conductors for clamping (additional connection)

Connection type, additional connection PUSH IN

Conductors for clamping (rated connection)

Clamping range, max.	16 mm ²		
Clamping range, min.	0.5 mm ²		
Connection cross-section, stranded,	16 mm²		
max.			
Connection cross-section, stranded, min	n. 0.5 mm²		
Connection direction	top		
Number of connections	1		
Tube length for twin wire-end ferrule	Cross-section for conductor connection	min.	0.75 mm ²
		max.	1 mm ²
	Tube length	nominal	18 mm
	Cross-section for conductor connection	min.	1.5 mm ²
		max.	4 mm ²
	Tube length	min.	12 mm
		max.	18 mm



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Tube length for wire-end ferrule with plastic collar DIN 46228/4	Cross-section for conductor connection	min.	1.5 mm ²
		max.	4 mm ²
	Tube length	min.	18 mm
	Cross-section for conductor connection	min.	6 mm²
		max.	10 mm ²
	Tube length	min.	12 mm
		max.	18 mm
Tube length for wire-end ferrule without	Tube length	nominal	18 mm
plastic collar DIN 46228/1	Cross-section for conductor connection	min.	1.5 mm ²
		max.	10 mm²
Twin wire-end ferrules, max.	4 mm ²		
Twin wire-end ferrules, min.	0.5 mm ²		
Type of connection	PUSH IN		
Type of connection 2	PUSH IN		
Wire connection cross section AWG, max.	AWG 6		
Wire connection cross section AWG, min.	AWG 20		
Wire connection cross section, finely stranded, max.	10 mm ²		
Wire connection cross section, finely stranded, min.	0.5 mm ²		
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	10 mm ²		
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	0.5 mm ²		
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	10 mm ²		
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	0.5 mm ²		
Wire connection cross-section, solid core, max.	10 mm ²		
	0.5 mm ²		

General

Number of poles	1	Rail	TS 35
Standards	In accordance with IEC 60947-7-1	Wire connection cross section AWG, max.	AWG 6
Wire connection cross section AWG, min.	AWG 20		

Rating data

Rated cross-section	10 mm²	Poted voltage	800 V
nated cross-section	10 111111-	Rated voltage	800 V
Rated AC voltage	800 V	Rated DC voltage	800 V
Rated current	57 A	Current at maximum wires	57 A
Standards	In accordance with IEC	Volume resistance according to IEC	
	60947-7-1	60947-7-x	$0.56~\text{m}\Omega$
Pollution severity	3	Surge voltage category	III



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Classifications

ETIM 6.0	EC000897	ETIM 7.0	EC000897
ETIM 8.0	EC000897	ETIM 9.0	EC000897
ETIM 10.0	EC000897	ECLASS 9.0	27-14-11-20
ECLASS 9.1	27-14-11-20	ECLASS 10.0	27-14-11-20
ECLASS 11.0	27-14-11-20	ECLASS 12.0	27-14-11-20
ECLASS 13.0	27-25-01-19	ECLASS 14.0	27-25-01-19
ECLASS 15.0	27-25-01-19		

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Approvals

Approvals





	1
Approvals MAMID	https://mdcop.weidmueller.com/mediadelivery/rendition/900_319217/-T1z1mm-S800/ https://
	mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/ https://
	mdcop.weidmueller.com/mediadelivery/rendition/900_319240/-T1z1mm-S800/ https://
	mdcop.weidmueller.com/mediadelivery/rendition/900_319244/-T1z1mm-S800/ https://
	mdcop.weidmueller.com/mediadelivery/rendition/900_319246/-T1z1mm-S800/ https://
	mdcop.weidmueller.com/mediadelivery/rendition/900_319213/-T1z1mm-S800/ https://
	mdcop.weidmueller.com/mediadelivery/rendition/900_319260/-T1z1mm-S800/
ROHS	Conform

Downloads

Approval/Certificate/Document of Con-	· Attestation of Conformity
formity	DNVGL certificate
•	20-AV4BO-0271U
	CE Declaration of Conformity
	UKCA declaration of conformity
	Confirmation of Standards EN 45545-2_2020-10
Engineering Data	CAD data – STEP
User Documentation	AAP Terminal Blocks for control voltage distribution
	User Manual AXC 1.5-16




Weidmüller Interface GmbH & Co. KG


Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Drawings









Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Digital multimeters



Multimeters are capable of measuring a number of variables. Each instrument can measure voltage and resistance, as well as performing continuity and diode testing as standard.

In addition, the individual multimeters also feature extra measuring options such as current, frequency, capacitance and temperature. Digital multimeters have the advantage of a clear display which can be read easily and directly. With these instruments, mistakes arising from faulty conversion of the measuring ranges or misreading the display are a thing of the past.

General ordering data

Type ZUB MULTIMETER
Order No. 9205270000
GTIN (EAN) 4032248723522
Oty. 1 pc(s).

Version Multimeter

Marker holder



The marker holder offer the possibility of additional mounting of standard markers with a pitch of 5 or 5.1 mm. The angled holders can be optionally snaped together and could be mounted in all standard marking channels of the Klippon[®] Connect modular terminal blocks. Fitting marker types could be found under the respective accessories of the designation marking holder.

Туре	BZT 1 ZA WS 10/5	Version
Order No.	<u>1805520000</u>	Accessories, Marker holder
GTIN (EAN)	4032248270248	
Qty.	100 pc(s).	
Туре	BZT 1 WS 10/5	Version
Type Order No.	BZT 1 WS 10/5 1805490000	Version Accessories, Marker holder
	,	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/8 MC SDR	Version
Order No.	1856750000	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4032248400867	Weidmueller, To customer specification
Qty.	160 pc(s).	
Туре	DEK 5/8 PLUS MC SDR	Version
Type Order No.	DEK 5/8 PLUS MC SDR 1046370000	Version Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
	,	

Slotted screwdriver



VDE insulated screwdriver sets, for working on live parts up to 1000 V AC and 1500 V DC, DIN EN 60900. IEC 900. Each piece is "GS" safety tested. Blade made from fully hardened, high-alloy chromium-vanadium-molybdenum steel, gun-metal finish.

Туре	SDIS SLIM 0.6X3.5X100	Version
Order No.	2749610000	Mounting tool, Blade width (B): 3.5 mm, Blade length: 100 mm, Blade
GTIN (EAN)	4050118896350	thickness (A): 0.6 mm
Qty.	1 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessorie<u>s</u>

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type DEK 5/8 MC NE WS Version

Order No. 1856740000 Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

GTIN (EAN) 4032248400850 Weidmueller, white

Qty. 800 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

....

Accessories

WS 8/10



WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

General ordering data

Type WS-A 8/10 MM WS
Order No. 2619890000
GTIN (EAN) 4050118626193
Oty. 350 pc(s).

Version

WS, Terminal marker, 8 x 10 mm, Weidmueller, white

10 mm² to 2.5 mm²



The unique modular concept can be tailored to every type of machine. The potential distribution terminal blocks AAP are successful thanks to their uniform design with two possible constructions – alternating or grouped. In the grouped structure of the control voltage distribution, the potentials are located on different terminal blocks and thus form entire potential blocks.

General ordering data

 Type
 AAP12 2.5 LI RD
 Version

 Order No.
 1988290000
 Modular distribution terminals, PUSH IN, 2.5 mm², 800 V, 24 A, dark

 GTIN (EAN)
 4050118372779
 beige

 Qty.
 50 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

DEK 5/8 PLUS MC NE WS

1046350000

4032248782055

Qty. 800 pc(s). Version

Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

Weidmueller, white

Blank

Order No.

GTIN (EAN)



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Zseries. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with PrintJet CONNECT oder/or Plotter is possible.

- · Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

WS 10/8 PLUS MC NE WS

Order No. 1905950000

GTIN (EAN) 4032248528103

420 pc(s). Qty.

Version

WS, Terminal marker, 10 x 8 mm, Pitch in mm (P): 8.00 Weidmueller,



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

 Type
 DEK 5/5 PLUS MC NE WS
 Version

 Order No.
 1854490000
 Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

 GTIN (EAN)
 4032248393596
 Weidmueller, white

 Qty.
 1,000 pc(s).

2.5 mm²

2.5 mm² The plug-in cross-connections feature easy handling and quick installation. This saves a great deal of time during installation in comparison with screwed solutions.

Туре	ZQV 2.5N/7 RD	Version
Order No.	<u>2108810000</u>	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 7,
GTIN (EAN)	4050118448498	Pitch in mm (P): 5.10, Insulated: Yes, Width: 33.4 mm
Qty.	20 pc(s).	
Туре	ZQV 2.5N/3 RD	Version
Order No.	2108690000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 3,
GTIN (EAN)	4050118448535	Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm
Qty.	60 pc(s).	
Туре	ZQV 2.5N/9 RD	Version
Order No.	2108900000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 9,
GTIN (EAN)	4050118448474	Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm
Qty.	20 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Туре	ZQV 2.5N/10 RD	Version
Order No.	2108910000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 10,
GTIN (EAN)	4050118486018	Pitch in mm (P): 5.10, Insulated: Yes, Width: 48.7 mm
Qty.	20 pc(s).	Thornin IIII (1), 0.10, indiated. 100, width. 10.7 IIIII
Туре	ZQV 2.5N/4 RD	Version
Order No.	2108700000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 4,
GTIN (EAN)		
, ,	4050118448528	Pitch in mm (P): 5.10, Insulated: Yes, Width: 18.1 mm
Qty.	60 pc(s).	
Туре	ZQV 2.5N/5 RD	Version
Order No.	<u>2108710000</u>	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 5,
GTIN (EAN)	4050118448511	Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm
Qty.	20 pc(s).	
Туре	ZQV 2.5N/6 RD	Version
Order No.	2108720000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 6,
GTIN (EAN)	4050118448504	Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm
Qty.	20 pc(s).	
-	ZQV 2.5N/8 RD	Version
Туре	ZQV Z.5N/ 6 ND	version
Order No.	2108870000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8,
•	,	
Order No.	<u>2108870000</u>	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8,
Order No. GTIN (EAN)	2108870000 4050118448481	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8,
Order No. GTIN (EAN) Qty.	2108870000 4050118448481 20 pc(s).	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8, Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm
Order No. GTIN (EAN) Oty. Type	2108870000 4050118448481 20 pc(s). ZOV 2.5N/2 RD	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8, Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm Version
Order No. GTIN (EAN) Qty. Type Order No.	2108870000 4050118448481 20 pc(s). ZQV 2.5N/2 RD 2108470000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8, Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 2,
Order No. GTIN (EAN) Oty. Type Order No. GTIN (EAN)	2108870000 4050118448481 20 pc(s). ZOV 2.5N/2 RD 2108470000 4050118448542	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8, Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 2,
Order No. GTIN (EAN) Oty. Type Order No. GTIN (EAN) Oty.	2108870000 4050118448481 20 pc(s). ZOV 2.5N/2 RD 2108470000 4050118448542 60 pc(s).	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8, Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm
Order No. GTIN (EAN) Oty. Type Order No. GTIN (EAN) Oty. Type	2108870000 4050118448481 20 pc(s). ZOV 2.5N/2 RD 2108470000 4050118448542 60 pc(s). ZOV 2.5N/20 RD	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8, Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Version
Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty. Type Order No.	2108870000 4050118448481 20 pc(s). ZQV 2.5N/2 RD 2108470000 4050118448542 60 pc(s). ZQV 2.5N/20 RD 2108920000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8, Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 20,
Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN)	2108870000 4050118448481 20 pc(s). ZOV 2.5N/2 RD 2108470000 4050118448542 60 pc(s). ZOV 2.5N/20 RD 2108920000 4050118485899	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8, Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 20,
Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty.	2108870000 4050118448481 20 pc(s). ZOV 2.5N/2 RD 2108470000 4050118448542 60 pc(s). ZOV 2.5N/20 RD 2108920000 4050118485899 20 pc(s).	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8, Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm
Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty.	2108870000 4050118448481 20 pc(s). ZOV 2.5N/2 RD 2108470000 4050118448542 60 pc(s). ZOV 2.5N/20 RD 2108920000 4050118485899 20 pc(s). ZOV 2.5N/50 RD	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8, Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 50,
Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN)	2108870000 4050118448481 20 pc(s). ZOV 2.5N/2 RD 2108470000 4050118448542 60 pc(s). ZOV 2.5N/20 RD 2108920000 4050118485899 20 pc(s). ZOV 2.5N/50 RD 21090000000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8, Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Version Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm Version



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Zseries. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with PrintJet CONNECT oder/or Plotter is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

WS 10/8 PLUS MC SDR Туре 1906030000 Order No. 4032248528196 GTIN (EAN) 84 pc(s).

WS, Terminal marker, 10 x 8 mm, Pitch in mm (P): 8.00 Weidmueller,

To customer specification

A-Series

Qtv.



A partition plate is used for the optical separation of circuits or used for electrical isolation from neighbouring cross-connectors. In contrast to the end plate, the contour can be larger than the adjacent terminal blocks. However, it should not be smaller, as otherwise the required clearance and creepage distances within the application can no longer be maintained.

General ordering data

Туре Order No. 2489100000 GTIN (EAN) 4050118499315 50 pc(s). Qty.

Version

A-series, Partition plate



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

A-Series



Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General ordering data

Туре	AEB 35 SC/1 BK	Version
Order No.	<u>2475310000</u>	A-series, End bracket
GTIN (EAN)	4050118487114	
Qty.	50 pc(s).	
Туре	AEB 35 SC/1	Version
Order No.	1991920000	A-series, End bracket
GTIN (EAN)	4050118376722	
Qty.	50 pc(s).	
Туре	AEB 35 SCL/1 V0	Version
Order No.	<u>2661280000</u>	A-series, End bracket
GTIN (EAN)	4050118702163	
Qty.	20 pc(s).	
Туре	AEB 35 SCL/1 VO BK	Version
Order No.	<u>2661300000</u>	A-series, End bracket
GTIN (EAN)	4050118702187	
Qty.	20 pc(s).	
Туре	AEB 35 SCL/1 V0 GY	Version
Order No.	<u>2661290000</u>	A-series, End bracket
GTIN (EAN)	4050118702170	
Qty.	20 pc(s).	

A-Series



Warning covers with a flash symbol provide more safety for man and machine. They are used where external voltage must be indicated within the application.

Туре	AAM 10 YE FLASH	Version
Order No.	<u>2635580000</u>	Terminal marker, 14 x 10 mm, yellow
GTIN (EAN)	4050118674521	
Qty.	40 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

A-Series



Uniform inspection and test taps, consistent crossconnections, efficient markers, and timesaving PUSH IN connection technology make the A-Series particularly future-proof. The innovative design with clearly delineated functional areas and coloured pushers ensures maximum connection and maintenance safety.

General ordering data

Type AEP AP12
Order No. 1988300000
GTIN (EAN) 4050118372786
Oty. 20 pc(s).

Version A-series, End plate

DEK 5/8



WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

General ordering data

 Type
 DEK 5/8 MM WS
 Version

 Order No.
 2007130000
 Dekafix, Terminal marker, 5 x 8 mm, Weidmueller, white

 GTIN (EAN)
 4050118392012

 Qty.
 500 pc(s).