Charging cable

LL 5m T2



LL 5m T2

Charging cable

Productnumber: 59180901
Dimensions: 12,8 x 5000 x 12,8 mm

Charging cable – AC charging cable with Type 2 charging plug in accordance with IEC 62196 and open cable ends, with cap, cable construction 5 x 2.5 mm² + 1 x 0.5 mm², IP54 (with cap), charging power up to max. 11 kW (3-phase), charging current up to max. 16 A, for installation on a Spelsberg Wallbox

5m length with Type 2 plug

IP54 400V AC

Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

max. charging power:	11 kW
max. charging current:	16 A
System side connection:	3-phase
Rated operating voltage AC:	400 V
Charging mode (IEC 61851):	3 C
Long charging cable:	5 m
Connector plug:	Type 2
Type of protection:	IP54
Rated current:	16 A
Number of power contacts:	5
Number of signal contacts:	2
Signal contacts rated current:	2 A
Signal contacts rated voltage:	30 V
Cable type:	straight

Colours

Accessory colour:	deep black

Dimensions

Width:	12.8 mm
Length:	5000 mm
Height:	12.8 mm
Diameter:	12.8 mm
Weight:	1.68 kg

Material characteristics

UV-resistant:	yes

Ambient conditions

max. relative humidity 25°C:	95 %

Ambient conditions

max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Sales Information

EAN:	4013902673636
ETIM Class:	EC002897
Custom tariff number:	85444290
Minimum order quantity:	1

Material

Accessory material:	insulating material