

Data sheet

MC274-4W 230 V AC


Page 1/7

P/N
110017051407
EAN 4251122194894
2026/09/28
Version: J


Illustrations



Wiring diagram



Diagramm



See enlarged drawings at the end of document

Product specification

Compact, pluggable relay for industrial use.

- Socket pins as soldering lugs
- Mechanical switch position display
- With manual test button
- Cadmium-free contacts
- LED-Indicator



Data sheet

MC274-4W 230 V AC

Page 2/7

P/N

110017051407

EAN 4251122194894

2026/09/28

Version: J

Technical Data

Supply

Operating voltage	230 V AC -10% ... +10%
Power consumption (max.)	7 mA
Response time typical	10 ms
Release time typical	8 ms
Coil resistance	16 kOhm
Power consumption coil	1,6 VA

Outputs

Contacts	4 changeover contacts
Contact material	AgNi
Switching capacity (max.)	1500 VA
Switching frequency	1200 switching cycles/h
Switching voltage (max.)	250 V AC
Switching voltage (min.)	10 V at 30 mA
Switching current (min.)	5 mA
Switching capacity (min.)	300 mW
Continuous Current	7 A
Switch-on current	12 A
Switching capacity	
Switching capacity AC 1	7 A / 230 V AC (VDE), 6 A / 250 V AC
Switching capacity AC 14 (at 120 V)	0,6 A (D300)
Switching capacity AC 14 (at 240 V)	0,3 A (D300)
Switching capacity AC 15 (at 120 V)	1.5 A
Switching capacity AC 15 (at 240 V)	0,75 A (C300)0,75 A (C300)
Breaking capacity (resistive load)	
Mechanical life	1x10 ⁷ switching cycles
Indicator	LED and mechanical

Insulation coil - contact set

Nominal voltage of the power supply system	250 V AC
Overvoltage category	II
Degree of pollution	2
Rated test voltage	2.5 kV
Type of insulation	basic insulation



Data sheet

MC274-4W 230 V AC

Page 3/7

P/N
110017051407
EAN 4251122194894
2026/09/28
Version: J

Technical Data

Housing

Dimensions

Dimension (W x H x D)	21 mm x 35.5 mm x 27.4 mm
Dimension (W x H x D)	0.827 in. x 1.398 in. x 1.079 in.
Weight	35 g
Mounting style	pluggable
Mounting position	any
Apposition	without distance
Connection type	plug-in connection

Protection category according to IEC 60529

Protection category (acc. to EN 116000-3)	RT I
---	------

Climatic Data

Operating

Temperature - Operating °C	-40 °C - 55 °C
Temperature - Operating °F	-40 °F - 131 °F

Storage

Temperature - Storage °C	-40 °C - 85 °C
Temperature - Storage °F	-40 °F - 185 °F

Environment

Relative humidity	max. 85 % non-condensing
-------------------	--------------------------

Power loss

Power loss (typical) coil	1.6 W
Power loss (typical) Contact rate	0.4 W

Classifications

ETIM 7.0	EC001437
ETIM 8.0	EC001437
ETIM 9.0	EC001437
ETIM 10.0	EC001437

Data sheet

Page 4/7

MC274-4W 230 V AC

P/N

110017051407

EAN 4251122194894

2026/09/28

Version: J

Technical Data

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.



Data sheet
MC274-4W 230 V AC

Page 5/7

P/N
110017051407
EAN 4251122194894
2026/09/28
Version: J

Accessories

P/N	Designation
110175	Socket 14 poles
110178	Socket 14 poles for electronic modules
110185	Socket 14 poles with spring-loaded terminals


Data sheet
MC274-4W 230 V AC

Page 6/7


P/N
110017051407
EAN **4251122194894**
2026/09/28
Version: J

Illustrations

Wiring diagram



Diagramm



Data sheet MC274-4W 230 V AC

Page 7/7

P/N
110017051407
EAN 4251122194894
2026/09/28
Version: J

Illustrations

Diagramm

