

Socket outlet combination

## STV 904-K



### STV 904-K

Socket outlet combination

**CUSTOMIZABLE**

Productnumber: 72940401

Dimensions: 200 x 200 x 122 mm

Socket outlet combination, protection class IP44, ready for connection, according to EN 61439-3, high mechanical strength, temperature-resistant, can be combined

Cable insertions:

Top: Pre-embossing 8 x M20, 1 x M25/32

Bottom: Pre-embossing 8 x M20, 1 x M25/32

Rear: Pre-embossing 2 x M20/25

**available modules: 8**

**equipped with:**

- 4 x Miniature circuit breaker B16A, 1-pin
- 1 x Residual Current Circuit Breaker (RCCB), 25/0.03A, 4-pole, type A
- 4 x SCHUKO® plug socket (on side), 230V

**Accessories supplied:**

Attachment bushes: 2x M25, 2x M32, sealing plugs, masking and labelling strips



## Technical Data

### Built-in devices

Residual Current Circuit Breaker (RCCB), 25/0.03A, 4-pole, type A:	1
Miniature circuit breaker B16A, 1-pin:	4
SCHUKO® plug socket (on side), 230V:	4

### electrical characteristics

Rated insulation voltage AC:	400 V
Protection class:	II
Type of protection:	IP44
Number of N-potentials:	1
Number of rows:	1
Number of modules:	8
Number of modules per row:	8
with N terminal:	yes
with PE terminal:	yes

### Colours

Base unit colour:	grey
Cover colour:	grey

### Dimensions

Width:	200 mm
Length:	200 mm
Height:	122 mm
Weight:	2.1 kg

### Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V2

### Material characteristics

Glow-wire flammability:	850 °C (EN 60695-2-11)
-------------------------	------------------------

### mechanical properties

Type of fastening:	Wall mounting
Impact strength:	IK08

### Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

### Sales Information

EAN:	4013902934577
ETIM Class:	EC000379
Custom tariff number:	85369095
Minimum order quantity:	1

### Material

Base unit material:	Polycarbonate, glass-fibre reinforced
Cover material:	Polycarbonate, glass-fibre reinforced
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced
Hinged window material:	Polycarbonate

**Cable gland**

