



Main

| | |
|---------------------------|--------------------|
| Range | Mureva |
| Product or component type | Interlocked socket |
| Device short name | Mureva socket |
| Plug, socket category | Low voltage |
| Poles description | 3P + E |
| Network type | AC |
| Outlet standard | Industrial |

Complementary

| | |
|--------------------------------|---|
| Mounting mode | Wall-mounted |
| [In] rated current | 16 A |
| [Ue] rated operational voltage | 380...415 V |
| Network frequency | 50/60 Hz |
| Ground lug clockwise position | 6 h |
| Protection type | Fuse |
| Fuse type | Cylindrical |
| Fuse size | 10.3 x 38 mm |
| Plug, socket material | Housing: self-extinguishing engineering polymer |
| Contacts material | Sleeves: nickel plated brass |
| Connections - terminals | Captive screws |
| Maximum cable cross section | 10 mm ² |
| Maximum cable outer diameter | 25 mm |
| Cable entry | Cable gland |
| Thread type | Pg 21 |
| Net weight | 1.24 kg |
| Base dimension | 103 x 255 mm |
| Height | 255 mm |
| Width | 103 mm |
| Depth | 150 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Red |

Environment

| | |
|---------------------------------------|---|
| Standards | IEC 60309-1 IEC 60309-2 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK09 conforming to EN 62262 |
| Fire resistance | 750 °C conforming to IEC 60695-2-11 |
| Relative humidity | 50 % at 40 °C 70 % at 30 °C 90 % at 20 °C |
| Ambient air temperature for operation | 35 °C (86400 s) -25...40 °C |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 10.5 cm |
| Package 1 Width | 17.0 cm |
| Package 1 Length | 26.0 cm |
| Package 1 Weight | 1.22 kg |

Offer Sustainability

| | |
|--|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| Minimum percentage of recycled plastic content | 50 |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|