



### Main

Range	Lineryg
Product name	Lineryg DS
Product or component type	Extension module
Comb busbar, distribution terminal block accessory type	Neutral bar
Poles description	1N
Accessory / separate part categor	Connection accessories

### Complementary

Distribution block outgoers	12 holes
Mounting support	Direct mounting on rear
Mounting mode	By screws
[Ue] rated operational voltage	230 V AC Ph/N
[Ie] rated operational current	125 A at 40 °C
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 61439-1
[Icw] rated short-time withstand current	3.5 kA for 1 s
[Ipk] rated peak withstand current	20 kA
Busbar length	125 mm
9 mm pitches	14
18 mm pitches	7
Height	20 mm
Width	125 mm
Depth	35 mm
Net weight	111 g
Connections - terminals	Supply: screw terminal 1 cable(s) 10...35 mm <sup>2</sup> rigid Supply: screw terminal 1 cable(s) 4...25 mm <sup>2</sup> flexible with cable end Distribution: screw terminal 7 cable(s) 2.5...25 mm <sup>2</sup> rigid Distribution: screw terminal 7 cable(s) 1.5...16 mm <sup>2</sup> flexible with cable end Distribution: screw terminal 4 cable(s) 1.5...16 mm <sup>2</sup> rigid Distribution: screw terminal 4 cable(s) 1.5...10 mm <sup>2</sup> flexible with cable end
Tightening torque	Supply: 2.5 N.m PZ2 screwdriver 9 mm Supply: 2.5 N.m flat screwdriver 9 mm Distribution: 2 N.m PZ2 screwdriver 7.5 mm Distribution: 2 N.m flat screwdriver 7.5 mm Distribution: 2 N.m PZ2 screwdriver 6.5 mm Distribution: 2 N.m flat screwdriver 6.5 mm
Range compatibility	ComPact

## Environment

Standards	IEC 60947-7-1 IEC 61439-2 EN/IEC 61439-1
Pollution degree	3
Overvoltage category	III
Dielectric strength	2500 V
Ambient air temperature for operation	-25...55 °C
Colour	White (RAL 9003)

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2 cm
Package 1 Width	3.5 cm
Package 1 Length	12.5 cm
Package 1 Weight	122 g
Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	12.832 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------