Combi connector

KST M32



KST M32

Combi connector

Productnumber: 19303201
Dimensions: 36,5 x 36,5 x 24,5 mm

Combination socket for connecting enclosures, polyethylene, grey, for wall thickness 1.5 - 4.0 mm

Length 25 mm, for vertical and horizontal connection of AK/AKi 24 distribution boards, ZKi meter enclosures and AKL/AKi 1-4 empty enclosures, for vertical connection of AK/AKi 09/12 distribution boards, as well as TK empty enclosures with M32 knock-outs

IP54

Created at 04.06.2026. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Type of protection:	IP54

Colours

Accessory colour:	light grey

Dimensions

Width:	36.5 mm
Length:	36.5 mm
Height:	24.5 mm
Weight:	0.044 kg

Material characteristics

UV-resistant:	no
Halogen free:	yes

Sales Information

EAN:	4013902917853
ETIM Class:	EC000451
Custom tariff number:	39269097
Minimum order quantity:	10