Junction box

Abox Pro 250-L EasyPrint



Abox Pro 250-L EasyPrint

Junction box

Productnumber: 425400EP
Dimensions: 252 x 202 x 120 mm

Junction box, with individual printing, configurable via spelsberg.com/easyprint, protection class IP66/IP67/IP69, nominal cross-section 25 mm², certified by VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), DLG (Ammonia resistance), DNV (Class: Ships and Offshore Installations), knockouts, M20/M25/M40/M50, (4 rear, 10 side), internal fixing points, for installation in industrial environments and unprotected outdoor areas

grey, Ui=1000 V AC, without terminals

Accessories supplied:
4 double membrane seals IP66 M40 sealing range 17 - 28 mm, cover retainer

Technical Data

electrical characteristics

Rated insulation voltage AC:	1000 V
Rated insulation voltage DC:	1000 V
Max. conductor cross section:	25 mm²
Protection class:	II
Type of protection:	IP66/IP67/IP69
Terminal type:	none

Colours

Base unit colour:	grey
Cover colour:	grey

Dimensions

Width:	252 mm
Length:	202 mm
Height:	120 mm
Inner length:	186 mm
Inner width:	236 mm
Inner height:	99 mm
Weight:	1.0341 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V0
Glow-wire flammability:	960 °C (EN 60695-2-11)

mechanical properties

Impact strength:	IK09
Sealable:	yes
Cover screw torque:	1.5 Nm

mechanical properties

Type of fastening:	Wall/ceiling mounting
Fastening:	internal fixing points

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	80 °C
24h ambient temperature:	60 °C
Installation location:	unprotected outdoor areas

Sales Information

EAN:	4013902698929
ETIM Class:	EC002600
Custom tariff number:	85389099
Minimum order quantity:	20


Material

Base unit material:	Polycarbonate, glass-fibre reinforced
Cover material:	Polycarbonate
Sealing material:	Thermoplastic elastomer
Cover screw material:	Stainless steel 1.4567 (V2A)

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))
Test mark:	DLG (Ammonia resistance)
Test mark:	DNV (Class: Ships and Offshore Installations)

Cable gland


3x M20/M40/M50
2x M20/M40/
M50
2x M20/M40
2x M25/M40
2x M20/M40/
M50
3x M20/M40/M50