




Hoofd

Range of product	Ecostruxure operator terminal Expert
Product or component type	Licentie
Formaat	Digitaal
Type software	Professional
Type licentie	Licentie vergrendeld knooppunt
Variant	Bouwtijd
Softwareversie	V3.5
Operating system requirement	Windows 10 64 bit
Systeemvereisten	8 GB RAM 30 GB ruimte op harde schijf
Taal	Engels Italiaans Chinees Spaans Frans Duits Portugees Koreaans

Complementair

Licentiecategorie	Permanent
Protocol communicatiepoort	CANopen slave Couzet Automation millenium 3 FBD Emerson Industrial Automation Modbus SIO master Control Techniques Modbus SIO master Emerson Process Management ROC Plus Ethernet Emerson Process Management ROC SIO HTTP IPsec Mitsubishi A Series Ethernet Mitsubishi FX series CPU direct Mitsubishi FX series Ethernet Mitsubishi iQ-R/F series Ethernet SLMP client Mitsubishi Q series CPU direct Mitsubishi Q series QnU CPU Ethernet Mitsubishi Q/QnA series serial Modbus Organization Modbus SIO ASCII master Modbus Organization Modbus SIO master Modbus Organization Modbus SIO slave Modbus Organization Modbus TCP master Modbus Organization Modbus TCP slave Omron CS/CJ/CP series host link Omron CS/CJ/CP/NX series Ethernet Omron CS/CJ/NJ/NX series Ethernet/IP OPC UA server Profibus DP slave Rockwell Automation Ethernet/IP Rockwell Automation DF1 Rockwell Automation DH485 Schneider Electric Modbus SIO master Schneider Electric Modbus TCP master Schneider Electric Modbus TCP master via USB Schneider Electric Machine expert network Schneider Electric PacDrive Schneider Electric Uni-Telway Schneider Electric Zelio Logic Siemens Simatic S7 Ethernet Siemens Simatic S7 MPI direct Siemens TIA portal Ethernet
Vorige software-versie	V3.4
Softwarefunctie	Professional screen design Simulation Alarms and events Blockly script Convertors Dockable windows interface environment Export with CSV and tab delimiter Import with CSV and tab format Data and operation logging Multi language development Multi language tables Object binding and properties Target binding and properties Project transfer (Ethernet, filesystem, USB cable) Recipes Screens (contents and folders) Security (levels, project, users) Project and application settings System keypad Text script Color themes Variable (arrays, binding, properties, structures) Online and integrated help system OPC UA server Web server API
Bereik compatibiliteit	Harmony GTU Harmony GTUX Harmony ST6 Harmony STM6 Harmony STO7 Harmony iPC
Hosting optie	On-premise
Licentie grootte	Single (1 station)

Processor requirement	Intel core i3 8th generation Intel core i5 8th generation
Resolutie display	1280 x 720 pixels HD