




Hoofd

Product or component type	Hulpcontact
Device short name	SDE
Bereik compatibiliteit	Masterpact Masterpact NT
Samenstelling signaleringscontacten	1 NO/NC

Complementair

Type hulpcontacten	Laag niveau
Mounting mode	Uittrekken
Onderbrekingsvermogen (A)	DC-12: 0,15 A at 250 V DC DC-12: 3 A at 24/48 V DC AC-12: 3 A at 24/48 V AC 50/60 Hz AC-12: 3 A at 240 V AC 50/60 Hz DC-12: 0,3 A at 125 V DC AC-12: 3 A at 380 V AC 50/60 Hz
Minimale belasting	2 mA bij 15 V

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3,0 cm
Package 1 Width	6,0 cm
Package 1 Length	12,0 cm
Package 1 Weight	45,0 g

Duurzaamheid van het aanbod

EU-richtlijn RoHS	Voldoet pro-actief (Product valt niet onder de EU RoHS juridische scope) EU-verklaring RoHS
Vrij van giftige zware metalen	Ja
Kwikvrij	Ja
RoHS-regulering China	RoHS-verklaring China
Informatie over RoHS-vrijstelling	Ja

contractuele waarborg

Garantie	18 months
----------	-----------