Meter housing

# AKi-Z 403-eHZ



## AKi-Z 403-eHZ

**Meter housing**

CUSTOMIZABLE

Productnumber: 75211001
Dimensions: 300 x 600 x 210 mm

Meter housing, with transparent cover, standard version sealable, with assembled BKE-I for electronic domestic supply meter, standard version sealable consumer space at the top, with 35 mm standard rails and PE/N double terminals, standard version sealable consumer space at the bottom, with 35 mm standard rails and 5-pole HA terminal 25/16 mm², With double membrane seals, Sealing and insulating plugs

IP54 IP65 IK08

# Technical Data

## electrical characteristics

| | |
|---|---|
| Protection class: | II |
| Type of protection: | IP54/IP65 |
| UL Type Rating: | not specified |

## Dimensions

| | |
|---|---|
| Width: | 300 mm |
| Length: | 600 mm |
| Height: | 210 mm |
| Weight: | 4.97 kg |

## Material characteristics

| | |
|---|---|
| UV-resistant: | yes |
| Halogen free: | yes |
| Flammability class according with UL94: | V2 |
| Glow-wire flammability: | 850 °C (EN 60695-2-11) |

## mechanical properties

| | |
|---|---|
| Type of fastening: | Surface mounting |
| Impact strength: | IK08 |

## Ambient conditions

| | |
|---|---|
| max. relative humidity 25°C: | 95 % |
| max. relative humidity 40°C: | 50 % |
| Min. ambient temperature: | -35 °C |
| Max. ambient temperature: | 80 °C |
| 24h ambient temperature: | 60 °C |
| Installation location: | protected outdoor areas |

## Sales Information

| | |
|---|---|
| EAN: | 4013902983032 |

## Sales Information

| | |
|---|---|
| ETIM Class: | EC000248 |
| Custom tariff number: | 85369095 |
| Minimum order quantity: | 1 |

## Material

| | |
|---|---|
| Base unit material: | Polycarbonate |
| Cover material: | Polycarbonate |
| Sealing material: | Polyurethane |
| Cover screw material: | Polyamide, glass-fibre reinforced |