

Data sheet

LF-F-CI4 LON


Page 1/7

P/N
110860133270
EAN 4251394620824
2026/09/24
Version: K


Illustrations



Principle diagram



Wiring diagram



See enlarged drawings at the end of document

Product specification

The LON module with analog inputs was developed for decentralized switching tasks. It is suitable for detecting 4 currents and 4 voltages of, for example, active temperature sensors, electrical vent and mixing valves, valve positions, etc. The inputs can be scanned by SNVT network variables. Suitable for decentralized mounting on TH35 rails according to IEC 60715 in electrical distribution cabinets.

- Connection with spring clamp terminal blocks (push-in)

Data sheet

LF-F-CI4 LON

Page 2/7

P/N
110860133270
EAN 4251394620824
2026/09/24
Version: K

Technical Data

Approvals



Open Energy Management Equipment 34TZ

RS485 interface

Protocol	TP/FT-10, free topology
Neuron	FT5000
Data format	Standard network variables (SNVT)
Transmission parameters	
Transmission rate	78 Kbit/s
Line topology	2700 m / 64 nodes
Free topology	500 m / 64 nodes
Cabling	Twisted Pair

Supply

Operating voltage	24 V AC/DC +/- 10 % (SELV)
Power consumption	
Power consumption AC (max.)	67 mA
Power consumption DC (max.)	24 mA
Duty cycle relative	100 %
Recovery time	550 ms

Inputs

Analog inputs	4, individually configurable
Current range	0 (4) - 20 mA DC (adjustable)
Resolution current input	0,05 mA
Error current input	1 %
Resistance range	10 kOhm
Voltage range	0 V - 10 V DC
Resolution voltage input	10 mV



Data sheet

LF-F-CI4 LON

Page 3/7

P/N
110860133270
EAN 4251394620824
2026/09/24
Version: K

Technical Data

Housing

Dimensions

Dimension (W x H x D)	35 mm x 69.3 mm x 60 mm
Dimension (W x H x D)	1.378 in. x 2.728 in. x 2.362 in.
Weight	84 g
Mounting style	Standard rail TH35
Mounting position	any
Apposition	The maximum quantity of LON modules connected side-by-side is limited to 15 or to a maximum power consumption of 2 Amps (AC or DC) per connection to the power supply. For any similar block of additional modules a separate connection to the power supply is necessary, without distance
Connection type	Spring clamp terminal blocks
Indicator	green and yellow LED

Terminal blocks

Supply and bus

Terminal block	4-pole
Solid wire (AWG)	max. 1.5 mm ² / max. 16 AWG
Stranded wire (AWG)	max. 1 mm ² / max. 18 AWG
Wire diameter	min. 0.3 mm max. 1.4 mm

Module connection

Wire cross section solid	0.2 mm ² - 2.5 mm ² / AWG 24-14
Wire cross section multi	0.25 mm ² - 2.5 mm ² / AWG 24-12
Wire cross section with wire ferrule	0.25 mm ² - 1.5 mm ² / AWG 24-16
Stripping length (min.)	8 mm
Protection circuit	Polarity reversal protection for DC operating voltage

Material

Color	gray
Material - Terminal block	Polyamid 6.6 V0
Material - Covers	Polycarbonat

Data sheet

LF-F-CI4 LON

Page 4/7

P/N
110860133270
EAN 4251394620824
2026/09/24
Version: K

Technical Data

Protection category according to IEC 60529

Protection category - housing (acc. to IEC 60529)	IP40
Protection category - terminal blocks (acc. to IEC 60529)	IP20

Climatic Data

Operating

Temperature - Operating °C	-5 °C - 55 °C
Temperature - Operating °F	23 °F - 131 °F
Relative humidity	max. 85 % non-condensing

Storage

Temperature - Storage °C	-20 °C - 70 °C
Temperature - Storage °F	-4 °F - 158 °F

Classifications

ETIM 7.0	EC000794
ETIM 8.0	EC000794
ETIM 9.0	EC000794
ETIM 10.0	EC000794

Software and additional documents

Software and documentation	Further documentation is available for free download at www.metz-connect.com
----------------------------	--

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.

Data sheet
LF-F-CI4 LON

Page 5/7

P/N
110860133270
EAN 4251394620824
2026/09/24
Version: K

Accessories

P/N	Designation
110214	U10 USB Network Interface - TP/FT-10 Channel
110369	Terminal block Type 259
11056170	Power supply NG4-F 24 V DC
11087913	LF-FAM LON
31135104	Typ 135 RIACON 135_3.5


Data sheet LF-F-CI4 LON

Page 6/7


P/N
110860133270
EAN 4251394620824
2026/09/24
Version: K

Illustrations

Dimensional drawing



Wiring diagram



Data sheet LF-F-CI4 LON

Page 7/7

P/N
110860133270
EAN 4251394620824
2026/09/24
Version: K

Illustrations

Principle diagram

