Large conduit box

U 120 GRO-3-O



U 120 GRO-3-O

Large conduit box

Productnumber: 97371401
Dimensions: 74 x 74 x 133 mm

Large conduit box , with open front section for special magnetic clip optimised for prefabricated parts, for ceiling slab thickness up to 7.5 cm, with M5 threaded bushing (load capacity 10 kg) to hold ceiling hook, protection class IP30, rated insulation voltage: 400V AC, Halogen free

3-part, for Spelsberg HM P 71 (98498001), magnet installation, membrane for perforation, sealing range M16 - M32

Created at 04.06.2026. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Type of protection:	IP30
Suitable for:	Concrete construction
UL Type Rating:	not specified

Colours

Base unit colour:	green
Cover colour:	other

Dimensions

Width:	74 mm
Length:	74 mm
Height:	133 mm
Inner height:	114 mm
Weight:	0.0769 kg

Material characteristics

Halogen free:	yes
Glow-wire flammability:	650 °C (EN 60695-2-11)

mechanical properties

Type of fastening:	magnet installation
Type of fastening:	Concrete construction

Ambient conditions

max. relative humidity 25°C:	- %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Sales Information

EAN:	4013902656134
ETIM Class:	EC002601
Custom tariff number:	39269097
Minimum order quantity:	1

Material

Base unit material:	Polypropylene
Cover material:	Polypropylene

Accessories

97822301 - IBT LZA-23 - Hole punch

97821801 - IBT LZA-18 - Hole punch

97820001 - IBT LZA-OE - Hole punch

98498001 - HM P 71 - IBT Accessories

97912401 - DH 125-M5 - ceiling hook

92510301 - VD-67-O - sealing plate

19599501 - LFR - Stepped drill

97022501 - RVB 25 - Conduit coupling

Cable gland

