
# AS425 LED WIDE FLOOD REFLECTOR

## Part number 8425483173410








IP 20 | CLASS I | CE | EAC

### Description

LED track light for indoor, comprising:
- Extruded aluminium profile and die-cast aluminium spotlight housing, powder-coated
- Tilting and turning spotlight head
- High-brilliance spherical faceted reflector for maximum performance and neutral colour rendering index
- Bayonet-closure ring for a toolless replacement of the reflector and the louvre
- Reflector in Wide Flood design
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Universal tri-phase adaptor included
- Built-in driver
- Quick and toolless installation
- Clear safety glass
- The luminaire is suitable for installation on standard tracks such as EUROSTANDARD PLUS®

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
**PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy**
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

**info.it@pil.lighting**
www.performanceinlighting.com

## Product data

| | | | |
|---|---|---|---|
| **ETIM Group:** | EG000027 | **ETIM Class:** | EC001744 |

## General information

| | | | |
|---|---|---|---|
| **Lampholder:** | LED | **Light source:** | LED |
| **Lightsource lumen output [lm]:** | 2890 | **Luminaire lumen output [lm]:** | 2280 |
| **Luminaire wattage [W]:** | 20 W | **Luminous efficacy [lm/W]:** | 114 |
| **CRI:** | 80 | **Colour temperature [K]:** | 4000 |
| **Colour / Finishing:** | WH-RAL9010 / White RAL9010 / Textured | **IP degree of protection:** | IP20 |
| **Impact resistance / impact energy:** | IK02 0.2J xx0 | **Protection class:** | I |
| **Optic:** | C/MW - Circular Medium-Wide | **Beam angle:** | 2 x 33° |
| **Net weight [kg]:** | 0.984 | **Overall diameter [mm]:** | 95 |
| **Overall length [mm]:** | 119 | **Overall width [mm]:** | 95 |
| **Overall height [mm]:** | 208 | | |

## Mechanical features

| | | | |
|---|---|---|---|
| **Shape:** | Round ≤ 150 mm | **Housing material:** | Aluminium |
| **Diffuser material:** | Transparent glass | **Glow wire test [°C]:** | 650 °C |

## Electrical features

| | | | |
|---|---|---|---|
| **Voltage type:** | AC | **Input voltage [V AC]:** | 220/240 |
| **Input frequency [Hz]:** | 50/60 | **Power factor / COS Φ:** | >0.9 |
| **C10 1.5 mm²:** | 28 | **C16 2.5 mm²:** | 46 |
| **B10 1.5 mm²:** | 28 | **B16 2.5 mm²:** | 46 |
| **EEI:** | A2 | | |

## Installation

| | | | |
|---|---|---|---|
| **Application area:** | Indoor lighting | **Mounting type:** | Tracklight |
| **Min. ambient temperature [°C]:** | 10 | **Max. ambient temperature [°C]:** | 40 |
| **Min. distance from lighted object [m]:** | 0.10 | | |

## Light features


| | | | |
|---|---|---|---|
| **MacAdam:** | 3 | **Lumen maintenance:** | L80B10@75000h |
| **Distribution of light emission:** | Direct | **DFF - Downward Flux Fraction [%]:** | 100 |
| **UFF - Upward Flux Fraction [%]:** | 0 | | |

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
**PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy**
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211


**info.it@pil.lighting**
www.performanceinlighting.com

## Photometric data




## Optional accessories

AS425 LED



**8414900**

Frosted safety glass pane



**8433961**

Food glass filter for meat products



**8433962**

Food glass filter for bakery products



**8433963**

Food glass filters for fruits and cheese



**8433964**

Food glass filter for vegetables



**8433965**

Food glass filter for fish products

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
**PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy**
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

**info.it@pil.lighting**
www.performanceinlighting.com