



UK Declaration of Conformity

UK1006187-0

1.Product Identification

Object of the declaration:

Product:

Reference:

DC Electric Vehicle Charging Station
Schneider StarCharge Fast 60
See Annex

2.0 This declaration of conformity is issued under the sole responsibility of the manufacturer.

SCHNEIDER eSTAR
35 Rue Joseph Monier
92500 Rueil-Malmaison France

3.0 We Undersigned SCHNEIDER eSTAR declare that Schneider Electric branded products, when subject to correct installation, Maintenance and use confirming their intended purpose, according to applicable regulations and standards in the country where they are installed, to the supplier's instructions and to accepted rules of the art comply with essential requirements of following Statutory Inventories and is also in conformity with the relevant union harmonization legislation.

4.0

Statutory Inventory with Amendments	Harmonized Standards/Other Technical Specification
SI 2012 No. 3032 - The RoHS Regulation	BS EN IEC 63000:2018
SI 2017 No. 1206 - The Radio Equipment Regulations	BS EN IEC 61851-1:2019, BS EN 61851-23:2014, BS EN 61851-24:2014
	BS EN 61000-6-2:2005 and BS EN IEC 61000-6-2:2019, BS EN 61000-6-4:2007+A1:2011 and BS EN IEC 61000-6-4:2019, BS EN IEC 61851-21-2:2021, EN 301 489-1 V1.9.2 (2011-09) and EN 301 489-1 V2.2.3 (2019-11), EN 301 489-3 V2.3.2 (2023-01), EN 301 489-17 V3.2.4 (2020-09) and EN 301 489-17 V3.3.1 (2024-09), EN 301 489-52 V1.2.1 (2021-11) and EN 301 489-52 V1.3.1 (2024-11), BS EN IEC 62311:2020
	EN 300 330 V2.1.1 (2017-02), EN 301 511 V12.5.1 (2017-03), EN 301 908-1 V15.2.1 (2023-01), EN 301 908-2 V13.1.1(2020-06), EN 301 908-13 V13.2.1 (2022-02) and EN 301 908-13 V13.3.1 (2024-10), EN 300 328 V2.2.2 (2019-07)

5.0 Signed on behalf of:

Place and Date:

Signature:

Name / Title:

Schneider Electric Limited

Telford, UK, 12.06.2025

A578D60923D7459...

David Williams

VP Marketing UK & Ireland

UK Declaration of Conformity

UK1006187-0

Annex

Product	Short Description	Ratings
EVD2SxxTyyzzaa-bb	DC Electric Vehicle Charging Station	Input: 380 ~ 415Vac $\pm 10\%$, 3-phase, 50/60Hz, L1+L2+L3+N+PE, Output: 150-1000Vdc, 200Adc Max, 60kW Max

Model Definition

EVD2SxxTyyzzaa-bb			
Small letter	Description	Value	Definition
xx	Power	60	60kW
		63	30kW
T	Touchscreen (HMI)	/	/
yy	Connector	0B	CCS2
		BB	CCS2+CCS2
zz	Cable length	blank	Default usable length is 5m with cable management
		C5	5m without cable management
		C7	7.5m without cable management
aa	Credit card reader	blank	without payment terminal
		CC	with payment terminal
bb	Marketing	blank	Europe
		-AN	Australia/New Zealand
		-F	France
		-G	Germany
		-T	Turkey
		-IEC	Rest of world

UK Declaration of Conformity

Photographs

