

Data sheet

MARK-E08 230 V AC, 24 V AC/DC

Page 1/8

P/N

110657

EAN 4250184122876


2026/09/23

Version: K


Illustrations



Dimensional drawing



Wiring diagram



See enlarged drawings at the end of document

Product specification

Multifunctional timer relay with incorporated coding switches to set functions. The time is set by means of a linear potentiometer on a relative scale.

- Connection with screw type terminal blocks
- Eight adjustable time ranges from 0.15 s to 10 h
- Five selectable functions
 1. On-delayed
 2. Off-delayed
 3. Making-pulse interval
 4. Flashing for pause start
 5. Flashing for pulse start

Data sheet

MARK-E08 230 V AC, 24 V AC/DC

Page 2/8

P/N
110657
EAN 4250184122876
2026/09/23
Version: K

Technical Data

Supply

Operating voltage	230 V AC / 24 V AC/DC -10% ... +10%
Time Ranges	
Time range adjustable	0.15 s - 10 h

Outputs

Contacts	1 changeover contact
Contact material	AgSnO ₂
Switching voltage (max.)	250 V AC
Continuous Current	6 A
Switching frequency	1200 switching cycles/h
Mechanical life	1x10 ⁷ switching cycles
Electrical life	1x10 ⁵ switching cycles
Recovery time	
Recovery time (control contact)	> 50 ms
Indicator	green and red LED

Insulation coil - contact set

Nominal voltage of the power supply system	230 / 400 V AC
Overvoltage category	III II
Degree of pollution	2 2
Rated test voltage	4 kV 2.5 kV
Type of insulation	basic insulation reinforced insulation

Housing

Dimensions	
Dimension (W x H x D)	22.5 mm x 61.3 mm x 60 mm
Dimension (W x H x D)	0.886 in. x 2.413 in. x 2.362 in.
Weight	70 g
Mounting style	Standard rail TH35
Mounting position	any
Apposition	without distance
Connection type	Screw type terminal blocks

Data sheet

MARK-E08 230 V AC, 24 V AC/DC

Page 3/8

P/N
110657
EAN 4250184122876
2026/09/23
Version: K

Technical Data

Terminal blocks

Wire cross section solid	0.34 mm ² - 2.5 mm ² / AWG 22-12
Wire cross section multi	0.25 mm ² - 2.5 mm ² / AWG 22-12
Wire cross section with wire ferrule	0.25 mm ² - 2.5 mm ² / AWG 22-12
Screw torque (max.)	0.5 Nm
Stripping length (min.)	8 mm

Material

Material - Housing	Polyamid 6.6 V0
Color	gray
Material - Terminal block	Polyamid 6.6 V0
Material - Covers	Polyamid 6.6 V0

Protection category according to IEC 60529

Protection category - housing (acc. to IEC 60529)	IP40
Protection category - terminal blocks (acc. to IEC 60529)	IP20

Climatic Data

Operating

Temperature - Operating °C	-10 °C - 55 °C
Temperature - Operating °F	14 °F - 131 °F
Relative humidity	max. 85 % non-condensing

Storage

Temperature - Storage °C	-25 °C - 70 °C
Temperature - Storage °F	-13 °F - 158 °F

Power loss

Power loss (typical)	1 W
----------------------	-----

Classifications

ETIM 7.0	EC001439
ETIM 8.0	EC001439
ETIM 9.0	EC001439
ETIM 10.0	EC001439

Data sheet

Page 4/8

MARK-E08 230 V AC, 24 V AC/DC

P/N

110657

EAN 4250184122876

2026/09/23

Version: K

Technical Data

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.



Data sheet

Page 5/8

MARK-E08 230 V AC, 24 V AC/DC

P/N

110657


EAN 4250184122876

2026/09/23

Version: K

Illustrations

Dimensional drawing



Wiring diagram

A1+	A3-	A2	A2
15	16	18	B1

A1+ - A2

operating voltage

230 V AC

A1+ - A3-

operating voltage

24 V AC/DC

A1+ - B1

control contact

15 - 16 - 18

output contact

1 changeover


Caution!

Terminal B1 is not isolated.




Illustrations

Circuit diagram



Function diagram



Data sheet
MARK-E08 230 V AC, 24 V AC/DC


Page 7/8

P/N
110657
 EAN 4250184122876
 2026/09/23
 Version: K

Illustrations


Function diagram

Flashing for pulse start




Function diagram

Making-pulse interval



Illustrations

Function diagram



Function diagram

