

**QL 2 WTL6/4FF****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image**

Similar to illustration

**General ordering data**

|            |                                                                                                                                        |
|------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Version    | Cross-connector (terminal), when screwed in, Silver grey, 41 A, Number of poles: 2, Pitch in mm (P): 11.00, Insulated: No, Width: 2 mm |
| Order No.  | <a href="#">1897010000</a>                                                                                                             |
| Type       | QL 2 WTL6/4FF                                                                                                                          |
| GTIN (EAN) | 4032248513987                                                                                                                          |
| Qty.       | 100 pc(s).                                                                                                                             |

**QL 2 WTL6/4FF****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 6 mm    | Depth (inches)  | 0.236 inch |
| Height     | 19.8 mm | Height (inches) | 0.78 inch  |
| Width      | 2 mm    | Width (inches)  | 0.079 inch |
| Net weight | 1.61 g  |                 |            |

**Temperatures**

|                     |                |                     |               |
|---------------------|----------------|---------------------|---------------|
| Storage temperature | -25 °C...55 °C | Ambient temperature | -5 °C...40 °C |
|---------------------|----------------|---------------------|---------------|

**Material data**

|          |      |        |             |
|----------|------|--------|-------------|
| Material | CuSn | Colour | Silver grey |
|----------|------|--------|-------------|

**System specifications**

|         |                 |
|---------|-----------------|
| Version | Cross-connector |
|---------|-----------------|

**Additional technical data**

|                          |                 |                     |                                         |
|--------------------------|-----------------|---------------------|-----------------------------------------|
| Explosion-tested version | No              | Installation advice | Feed-through (bushing), Direct mounting |
| Type of fixing           | when screwed in | Type of mounting    | when screwed in                         |

**Dimensions**

|                 |       |
|-----------------|-------|
| Pitch in mm (P) | 11 mm |
|-----------------|-------|

**General**

|                     |                                         |                 |   |
|---------------------|-----------------------------------------|-----------------|---|
| Installation advice | Feed-through (bushing), Direct mounting | Number of poles | 2 |
|---------------------|-----------------------------------------|-----------------|---|

**Rating data**

|               |      |
|---------------|------|
| Rated current | 41 A |
|---------------|------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ETIM 8.0    | EC000489    | ETIM 9.0    | EC000489    |
| ETIM 10.0   | EC000489    | ECLASS 9.0  | 27-14-11-40 |
| ECLASS 9.1  | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 | ECLASS 12.0 | 27-14-11-40 |
| ECLASS 13.0 | 27-25-03-03 | ECLASS 14.0 | 27-25-03-03 |
| ECLASS 15.0 | 27-25-03-03 |             |             |

**Environmental Product Compliance**

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

Creation date May 11, 2025 8:04:25 PM CEST

Catalogue status 26.04.2025 / We reserve the right to make technical changes.

### QL 2 WTL6/4FF

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Engineering Data   | <a href="#">CAD data – STEP</a>                 |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |
| Brochures          | <a href="#">CAT 1 TERM 16/17 EN</a>             |