Terminal rails

AK 14/28 PEN-S



AK 14/28 PEN-S

Terminal rails

Productnumber: 79021701
Dimensions: 286 x 37 x 29 mm

PE/N terminal strip, for installation in AK small distribution board with year of construction up until 2014, and in AKL/AKi empty enclosures.

PE/N-terminal each with 1 terminal point of 25 mm², 4 clamping points of 16 mm2 and 12 clamping points of 6 mm²

Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Rated operating voltage AC:	400 V
Number of poles:	2
shockproof:	No
Connection 1: Connection type:	Screws
Connection 1: Strip length:	12 mm
Connection 1: Clamping points per pole:	12
Connection 1: Suitable for Cu conductors:	1
Connection 1: Connectable conductor cross-section, single-wire (min):	6 mm²
Connection 1: Connectable conductor cross-section, single-wire (max):	16 mm²
Connection 2: Connection type:	Screws
Connection 2: Suitable for Cu conductors:	1
Connection 2: Connectable conductor cross-section, single-wire (min):	1.5 mm²
Connection 2: Connectable conductor cross-section, single-wire (max):	6 mm²

Dimensions

Width:	286 mm
Length:	37 mm
Height:	29 mm
Weight:	0.1364 kg

Material characteristics

Flammability class according with UL94:	V2
Glow-wire flammability:	960 °C (EN 60695-2-11)

mechanical properties

Connection 1: Tightening moment:	1.4 Nm
Connection 2: Tightening torque:	1.4 Nm

Sales Information

EAN:	4013902062652
ETIM Class:	EC001284
Custom tariff number:	85369010
Minimum order quantity:	1

Material

Insulating body material:	Thermoplastic

Accessories

79541301 - SR NS35 - Screw set