

LE1M35P722

Enclosed DOL starter, TeSys LE, 12-16A, 230V
AC coil, including 1 LC1K, LR2K, 2
pushbuttons, yellow indicator



Hoofd

Range	TeSys
Product name	TeSys LE
Device short name	LE1M
Product or component type	Geïsoleerde DOL-starter
Device application	Norm
Utilisation category	AC-3
Apparaatsamenstelling	Contacteur Aardingsklem Nulleider klem Thermisch overbelastingsrelais
Instelbereik thermische beveiliging	12...16 A
Motorvermogen kW	4 kW bij 240 V AC 50/60 Hz 7,5 kW bij 415 V AC 50/60 Hz 7,5 kW bij 380/400 V AC 50/60 Hz 3,7 kW bij 220/230 V AC 50/60 Hz
Spanning stuurkring	230 V AC 50/60 Hz
Besturingstype	Drukknop start groen I Drukknop stop/reset rood O

Complementair

Lokale signalering	In werking: LED (geel)
Nummer kabelinvoer	2 kabelingang: ISO20 bovenkant 2 kabelingang: ISO25 bovenkant 2 kabelingang: Pg 13 bovenkant 2 kabelingang: Pg 21 bovenkant 2 kabelingang: ISO20 basis 2 kabelingang: ISO25 basis 2 kabelingang: Pg 13 basis 2 kabelingang: Pg 21 basis 2 kabelingang: Pg 16 bovenkant 2 kabelingang: Pg 16 basis
Width	78 mm
Height	160 mm
Depth	108 mm
Net weight	0,6 kg

Omgeving

Materiaal	ABS (acrylonitrile butadiene-styrene)
IP beschermingsgraad	IP65 conform aan IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C
Milieu-eigenschappen	Standaard omgeving
Product certifications	UKCA

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8,000 cm
Package 1 Width	11,500 cm
Package 1 Length	16,500 cm
Package 1 Weight	581,000 g
Unit Type of Package 2	S02
Number of Units in Package 2	6
Package 2 Height	15,000 cm
Package 2 Width	30,000 cm
Package 2 Length	40,000 cm
Package 2 Weight	3,739 kg
Unit Type of Package 3	P06
Number of Units in Package 3	96
Package 3 Height	75,000 cm
Package 3 Width	80,000 cm
Package 3 Length	60,000 cm
Package 3 Weight	67,824 kg

Duurzaamheid van het aanbod

Duurzaamheids status van het aanbod	Green Premium product
REACH-regelgeving	REACH-verklaring
REACH vrij van SVHC	Ja
EU-richtlijn RoHS	Voldoet EU-verklaring RoHS
Vrij van giftige zware metalen	Ja
Kwikvrij	Ja
RoHS-regulering China	RoHS-verklaring China
Informatie over RoHS-vrijstelling	Ja
Milieu Profiel	Milieuprofiel Van Het Product
Circulair Profiel	Informatie Over Einde Levensduur
WEEE	Het product moet op markten van de Europese Unie worden afgevoerd volgens specifieke afvalinzamelingsregels en mag nooit in een gewone vuilnisbak terechtkomen.