

Socket outlet combination

STK-Z E16



STK-Z E16

Socket outlet combination

Productnumber: 73003001

Dimensions: 315 x 300 x 189 mm

Socket outlet combination, protection class IP44, Additional enclosure for easy combination with STK socket combinations or AK Air distributors with flange openings (AK-F), including combination flange AK3 KFL, without mounting flange

equipped with:

- 1 x CEE appliance inlet (on front), 16A, 400V, 5p



The high-quality STK socket combinations are easily expandable via the AK Air flange system and offer high installation comfort with the central connection terminal for the supply line. Fully wired and tested with series connection devices and sockets. The STK-Z additional enclosures can be easily combined with the small distributors AK-F 14-56; a combination flange is included. The flexible system is also the basis for customer-specific solutions deviating from the standard. A product that offers flexibility and adapts to your needs.

Technical Data

Built-in devices

| | |
|--|---|
| CEE appliance inlet (on front), 16A, 400V, 5p: | 1 |
|--|---|

electrical characteristics

| | |
|------------------------------|-------|
| Rated operating voltage AC: | 400 V |
| Rated insulation voltage AC: | 400 V |
| Protection class: | II |
| Type of protection: | IP44 |
| vented: | yes |
| Number of rows: | yes |
| Number of modules per row: | yes |

Colours

| | |
|-------------------|------|
| Base unit colour: | grey |
| Cover colour: | grey |

Dimensions

| | |
|---------------|--------|
| Width: | 315 mm |
| Length: | 300 mm |
| Height: | 189 mm |
| Inner width: | 295 mm |
| Inner height: | 106 mm |
| Weight: | 1.7 kg |

Material characteristics

| | |
|-------------------------|------------------------|
| UV-resistant: | yes |
| Halogen free: | yes |
| Glow-wire flammability: | 850 °C (EN 60695-2-11) |

mechanical properties

| | |
|---------------------|---------------|
| Type of fastening: | Wall mounting |
| Impact strength: | IK08 |
| Sealable: | yes |
| Cover screw torque: | 1.2 Nm |
| Flange variant: | yes |

Ambient conditions

| | |
|------------------------------|-------------------------|
| max. relative humidity 25°C: | 90 % |
| max. relative humidity 40°C: | 50 % |
| Min. ambient temperature: | -25 °C |
| Max. ambient temperature: | 40 °C |
| 24h ambient temperature: | 35 °C |
| Installation location: | protected outdoor areas |

Sales Information

| | |
|-------------------------|---------------|
| EAN: | 4013902689828 |
| ETIM Class: | EC000379 |
| Custom tariff number: | 85369095 |
| Minimum order quantity: | 1 |

Material

| | |
|-------------------------|---------------------------------------|
| Base unit material: | Polycarbonate, glass-fibre reinforced |
| Cover material: | Polycarbonate |
| Sealing material: | Polyurethane |
| Cover screw material: | Polyamide, glass-fibre reinforced |
| Hinged window material: | Polycarbonate |

Accessories

[73382001 - AK3 FL00 - Flange for AK-F](#)

[73382101 - AK3 FL01 - Flange for AK-F](#)

[73382201 - AK3 FL02 - Flange for AK-F](#)

[73382901 - AK3 KFL - Flange for AK-F](#)

[73352801 - AK-F 28 - Small distributions boards](#)

[73354201 - AK-F 42 - Small distributions boards](#)

[73355601 - AK-F 56 - Small distributions boards](#)

[73383001 - AK3 KS M50 - Combination cable gland](#)

Cable gland

