
Receptacle

# U 71 GRD-D



## U 71 GRD-D

**Receptacle**

Productnumber: 97104502
Dimensions: 71 x 71 x 50 mm

Receptacle, for extremely thin walls, only 45 mm deep, combinable with corresponding binocular-like connectors, protection class IP30, rated insulation voltage: 400V AC, certified by VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), Halogen free

**magnet and nail installation, membrane for perforation, sealing range M16 - M20, support spar compatible**

# Technical Data

## electrical characteristics

| | |
|---|---|
| Rated insulation voltage AC: | 400 V |
| Type of protection: | IP30 |
| UL Type Rating: | not specified |

## Colours

| | |
|---|---|
| Cover colour: | other |

## Dimensions

| | |
|---|---|
| Width: | 71 mm |
| Length: | 71 mm |
| Height: | 50 mm |
| Weight: | 0.041 kg |

## Material characteristics

| | |
|---|---|
| Halogen free: | yes |

## mechanical properties

| | |
|---|---|
| Type of fastening: | magnet and nail installation |

## Ambient conditions

| | |
|---|---|
| max. relative humidity 25°C: | - % |
| max. relative humidity 40°C: | 50 % |
| Min. ambient temperature: | -25 °C |
| Max. ambient temperature: | 40 °C |
| 24h ambient temperature: | 35 °C |

## Sales Information

| | |
|---|---|
| EAN: | 4013902887927 |
| ETIM Class: | EC002601 |
| Custom tariff number: | 39269097 |

## Sales Information

| | |
|---|---|
| Minimum order quantity: | 1 |

## Material

| | |
|---|---|
| Base unit material: | Polypropylene |
| Cover material: | Polypropylene |

## Certificates

| | |
|---|---|
| Test mark: | VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)) |

## Cable gland

