


date: 22/10/2026

GUELL 2.5+ A/W

Part number LTF1624FA840







IP 66 | CLASS I | ≤-40°C | FULL CUT OFF | ULR<1 | CIEn°3>95 | SPD 10kV | CE | EAC | UKCA

Description

LED floodlight for indoor and outdoor, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
- Anti-ageing custom moulded silicone sealing gasket(s)
- M20x1.5 cable gland for cables Ø10–Ø14 mm
- Stainless steel locking hardware
- Fully integrated stainless steel aluminium spring clips
- Powder-coated steel tiltable bracket
- Openable and maintainable luminaire (future-proof)
- Protected against power surges up to 10 kV
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Design by GIORGIO LODI

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Product data

ETIM Group:	EG000027	**ETIM Class:**	EC001744

General information

Lampholder:	LED	**Light source:**	LED
Lightsource lumen output [lm]:	31476	**Luminaire lumen output [lm]:**	25855
Luminaire wattage [W]:	193 W	**Luminous efficacy [lm/W]:**	134
CRI:	80	**Colour temperature [K]:**	4000
Colour / Finishing:	GR-94 / Metallic grey / Textured	**IP degree of protection:**	IP66
Impact resistance / impact energy:	IK07 3J xx5	**Protection class:**	I
Optic:	A40/W - Asymmetric Wide	**Net weight [kg]:**	6.484
Overall length [mm]:	355	**Overall width [mm]:**	425
Overall height [mm]:	85		

Mechanical features

Shape:	Rectangular	**Housing material:**	Aluminium
Diffuser material:	Glass	**Glow wire test [°C]:**	650 °C
Frontal exposed area [m²]:	0.03	**Lateral exposed area [m²]:**	0.03
Top exposed area [m²]:	0.14		

Electrical features

Voltage type:	AC	**Input voltage [V AC]:**	100/305
Input frequency [Hz]:	50/60	**Power factor / COS Φ:**	>0.9
Surge protection | Common [kV]:	10.000000	**Surge protection | Differential [kV]:**	6.000000
Inrush current [A/µs]:	120 / 200	**C10 1.5 mm²:**	5
C16 2.5 mm²:	9	**B10 1.5 mm²:**	3
B16 2.5 mm²:	5		

Installation

Application area:	Outdoor lighting	**Mounting type:**	Professional floodlight
Min. ambient temperature [°C]:	-40	**Max. ambient temperature [°C]:**	30
Min. distance from lighted object [m]:	1.00		

Light features

MacAdam:	3	**Lumen maintenance:**	L80B10@78000h
Distribution of light emission:	Direct	**Luminous Intensity Class:**	G*6
Zero light pollution (ULR = 0%):		**IPEA* (road lighting):**	A++
IPEA* (large areas, roundabouts):	A6+	**IPEA* (cycle-pedestrian):**	A3+

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com


IPEA* (green areas):	A3+	**IPEA* (historic city centers):**	A8+

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211


info.it@pil.lighting
www.performanceinlighting.com

Photometric data



Optional accessories


GUELL 2.5+



LTF1A3652

Louvre GUELL 2.5+

GR-94 / Metallic grey



LTF1A5603

Protective grid GUELL 2.5+

GS1



14012294

Steel 'U' bolt clamp for Ø 60-80 mm poles painted aluminium grey

GR-94 / Metallic grey



310966

Single pole top support GUELL 2.5

GR-94 / Metallic grey



310967

Double pole top support GUELL 2.5

GR-94 / Metallic grey

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com