Light fixture junction box

Q 4-L/sw



Q 4-L/sw

Light fixture junction box

Productnumber: 33420401
Dimensions: 56 x 40 x 23 mm

Light fixture junction box, protection class IP20, nominal cross-section 2.5 mm², Ui=230 V AC, certified by VDE (DIN EN 60598-1 (VDE 0711-1)), inserts with cable retention capacity, (4 side), for standard indoor installations, with cable retention, cable entry from above possible

black, without terminals

IP20 | 2,5² | IK07 | 230V AC

Technical Data

electrical characteristics

Rated operating voltage AC:	230 V
Rated operating voltage DC:	230 V
Rated insulation voltage AC:	230 V
Max. conductor cross section:	2,5 mm²
Protection class:	II
Type of protection:	IP20
UL Type Rating:	not specified

Colours

Base unit colour:	black
Cover colour:	black

Dimensions

Width:	56 mm
Length:	40 mm
Height:	23 mm
Weight:	0.012 kg

Material characteristics

UV-resistant:	no
Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability:	650 °C (EN 60695-2-11)

mechanical properties

Type of fastening:	Wall/ceiling mounting
Impact strength:	IK07
Sealable:	no

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	Indoors

Sales Information

EAN:	4013902707188
ETIM Class:	EC002600
Custom tariff number:	39269097
Minimum order quantity:	50

Material

Base unit material:	Polypropylene
Cover material:	Polypropylene

Certificates

Test mark:	VDE (DIN EN 60598-1 (VDE 0711-1))

Cable gland

