

KISC M3X20 SAK10 CU5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

**Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

General ordering data

| | |
|------------|------------------------------------|
| Version | SAK Series, Mounting screw, Copper |
| Order No. | 0377100000 |
| Type | KISC M3X20 SAK10 CU5 |
| GTIN (EAN) | 4008190060350 |
| Qty. | 100 items |

KISC M3X20 SAK10 CU5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Dimensions and weights

| | | | |
|------------|--------|-----------------|-------------|
| Depth | 4.8 mm | Depth (inches) | 0.189 inch |
| Height | 20 mm | Height (inches) | 0.7874 inch |
| Width | 4.8 mm | Width (inches) | 0.189 inch |
| Net weight | 1.26 g | | |

Temperatures

| | | | |
|---------------------|----------------|---------------------|---------------|
| Storage temperature | -25 °C...55 °C | Ambient temperature | -5 °C...40 °C |
|---------------------|----------------|---------------------|---------------|

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

Material data

| | | | |
|----------------|--------|----------------|---------------|
| Basic material | Copper | Surface finish | Miscellaneous |
| Colour | grey | | |

System specifications

| | |
|---------|-------------|
| Version | for busbars |
|---------|-------------|

Additional technical data

| | | | |
|--------------------------|-----------------|---------------------|-----------------|
| Type of fixing | when screwed in | Installation advice | Direct mounting |
| Explosion-tested version | No | | |

Dimensions

| | |
|-------------------------------------|---------|
| Metric size of the thread, external | 3.00 mm |
|-------------------------------------|---------|

General

| | | | |
|---------------------|-----------------|----------------|---------------|
| Installation advice | Direct mounting | Surface finish | Miscellaneous |
|---------------------|-----------------|----------------|---------------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC002848 | ETIM 9.0 | EC002848 |
| ETIM 10.0 | EC002848 | ECLASS 14.0 | 27-25-03-90 |
| ECLASS 15.0 | 27-25-03-90 | | |