



Hoofd

Range	TeSys
Device short name	LAD4
Product or component type	Onderdrukkingsmodule
Compatibiliteit product	3P LC1D09...D38 4P LC1DT20...DT40 4P LC1D098...D258 CAD32, CAD50

Complementair

Montagezone	Zijkant
Mounting mode	Met klemmen
Ontstoringstechnologie	RC-circuit
Spanning stuurkring	24...48 V AC
Maximum piekspanning	3 Uc
Net weight	0,012 kg

Omgeving

Standards	IEC 60947-5-1 EN 60947-5-1 CSA C22.2 Nr 60947-5-1 UL 60947-5-1 GB/T 14048,5
Product certifications	UL[RETURN]CSA
IP beschermingsgraad	IP2x conform aan IEC 60529
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...80 °C

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1,500 cm
Package 1 Width	8,000 cm
Package 1 Length	4,000 cm
Package 1 Weight	14,000 g
Unit Type of Package 2	S01
Number of Units in Package 2	70
Package 2 Height	15,000 cm
Package 2 Width	15,000 cm
Package 2 Length	40,000 cm
Package 2 Weight	1,185 kg
Unit Type of Package 3	P06
Number of Units in Package 3	2240
Package 3 Height	75,000 cm

Package 3 Width	60,000 cm
Package 3 Length	80,000 cm
Package 3 Weight	39,860 kg

Duurzaamheid van het aanbod

Duurzaamheids status van het aanbod	Green Premium product
REACH-regelgeving	 REACH-verklaring
REACH vrij van SVHC	Ja
EU-richtlijn RoHS	Voldoet  EU-verklaring RoHS
Vrij van giftige zware metalen	Ja
Kwikvrij	Ja
RoHS-regulering China	 RoHS-verklaring China
Informatie over RoHS-vrijstelling	 Ja
Milieu Profiel	 Milieuprofiel Van Het Product
Circulair Profiel	Geen specifieke recycling vereist
WEEE	Het product moet op markten van de Europese Unie worden afgevoerd volgens specifieke afvalinzamelingsregels en mag nooit in een gewone vuilnisbak terechtkomen.

contractuele waarborg

Garantie	18 months
----------	-----------