




Hoofd

Product or component type	Hulpcontact
Device short name	SDE
Bereik compatibiliteit	Masterpact Masterpact NW
Samenstelling signaleringscontacten	1 NO/NC

Complementair

Type hulpcontacten	Standaard
Mounting mode	Vast
Ith conventionele thermische stroom in vrije lucht	5 A
Onderbrekingsvermogen (A)	AC-12: 3 A at 690 V AC 50/60 Hz DC-12: 0,15 A at 250 V DC DC-12: 3 A at 24/48 V DC DC-12: 0,3 A at 125 V DC
Minimale belasting	100 mA bij 24 V

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3,5 cm
Package 1 Width	4,0 cm
Package 1 Length	7,3 cm
Package 1 Weight	64,0 g

Duurzaamheid van het aanbod

REACH-regelgeving	 REACH-verklaring
REACH vrij van SVHC	Ja
EU-richtlijn RoHS	Voldoet aan vrijstellingen
Kwikvrij	Ja
RoHS-regulering China	 RoHS-verklaring China
Informatie over RoHS-vrijstelling	 Ja

contractuele waarborg

Garantie	18 months
----------	-----------