

**SFC-DS 0/21 MC NE WS****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**SFC – SlimFix Clip MultiCard with two labelling fields**

For conductor markers, it is often required to quickly read the start and destination designation of the respective conductor. Here it makes sense to print both data directly on a marker.

The new SFC-DS markers are designed as MultiCards and are suitable for direct printing with our PrintJet printing system. Their two labelling areas allow multiple data to be printed on a single marker. The print data can be imported directly from CAE projects into the M-Print® PRO marking software. After printing, the markers are placed around the conductor and securely fixed with a special locking mechanism.

**General ordering data**

|            |                                                 |
|------------|-------------------------------------------------|
| Version    | Conductor and cable markers, 21 x 4.2 mm, white |
| Order No.  | <a href="#">2904980000</a>                      |
| Type       | SFC-DS 0/21 MC NE WS                            |
| GTIN (EAN) | 4099986918504                                   |
| Qty.       | 200 pc(s).                                      |

## SFC-DS 0/21 MC NE WS

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 3.2 mm  | Depth (inches)  | 0.126 inch |
| Height     | 21 mm   | Height (inches) | 0.827 inch |
| Width      | 4.2 mm  | Width (inches)  | 0.165 inch |
| Net weight | 0.409 g |                 |            |

## General data

|                                   |            |                                   |         |
|-----------------------------------|------------|-----------------------------------|---------|
| Colour                            | white      | Halogen                           | No      |
| Operating temperature range, max. | 100 °C     | Operating temperature range, min. | -40 °C  |
| Printed characters                | without    | Type of printing                  | neutral |
| UL 94 flammability rating         | UL 94, V-2 | Width                             | 4.2 mm  |

## Conductor and cable markers

|                               |                   |                                  |                   |
|-------------------------------|-------------------|----------------------------------|-------------------|
| Conductor O.D., max.          | 2.5 mm            | Conductor O.D., min.             | 1.5 mm            |
| Conductor cross-section, max. | 1 mm <sup>2</sup> | Cross-section for connected wire | 1 mm <sup>2</sup> |
| Halogen                       | No                |                                  |                   |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ETIM 8.0    | EC001530    | ETIM 9.0    | EC001530    |
| ETIM 10.0   | EC001530    | ECLASS 9.0  | 27-40-04-01 |
| ECLASS 9.1  | 27-40-04-01 | ECLASS 10.0 | 27-40-04-01 |
| ECLASS 11.0 | 27-28-11-02 | ECLASS 12.0 | 27-28-11-02 |
| ECLASS 13.0 | 27-28-11-02 | ECLASS 14.0 | 27-28-11-02 |
| ECLASS 15.0 | 27-28-11-02 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## Downloads

|            |                                          |
|------------|------------------------------------------|
| Catalogues | <a href="#">Catalogues in PDF-format</a> |
|------------|------------------------------------------|

**SFC-DS 0/21 MC NE WS**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

