Meter housing

AKi-Z 410 KK



AKi-Z 410 KK

Meter housing

CUSTOMIZABLE

Productnumber: 75841001
Dimensions: 300 x 600 x 210 mm

Meter enclosure, with grey cover, sealable as standard, with mounted meter cross for three-phase meters and meter fixing screws, with additional hinged window for operating a selective main switch, incl. 2 single-pole HA terminals 25/16 mm² for N and PE, with 35 mm standard rail for installation of a selective main switch, with double membrane seals, sealing and insulating plugs

IP54 IK08 400V AC

Technical Data

electrical characteristics

Rated operating voltage AC:	400 V
Protection class:	II
Type of protection:	IP54
UL Type Rating:	not specified

Dimensions

Width:	300 mm
Length:	600 mm
Height:	210 mm
Weight:	4.46 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability:	850 °C (EN 60695-2-11)

mechanical properties

Type of fastening:	Surface mounting
Impact strength:	IK08

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	80 °C
24h ambient temperature:	60 °C
Installation location:	protected outdoor areas


Sales Information

EAN:	4013902902729
ETIM Class:	EC000248
Custom tariff number:	85369095
Minimum order quantity:	1

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate, glass-fibre reinforced
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced
Hinged window material:	Polycarbonate

Cable gland


15 xM20
5x M20/M25
1x M32/M40
12x M20
3x M25/M32
1xM32/M40/
M50
12x M20
3x M25/M32
1xM32/M40/
M50
2x M20
2x M32/M40
1x M40/M50/
M63