Conduit elbow

ROK 20



ROK 20

Conduit elbow

Productnumber: 97042501
Dimensions: 33 x 52,5 x 54 mm

Conduit elbow, rated insulation voltage: 400V AC, Halogen free, Number of 30° insertions: 1

for 30° insertion to insert into conduit ferrule (small) 97051801, M20, sealing range M20

Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Suitable for:	Concrete construction

Dimensions

Width:	33 mm
Length:	52.5 mm
Height:	54 mm
Weight:	0.001 kg

Material characteristics

Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability:	650 °C (EN 60695-2-11)

Ambient conditions

max. relative humidity 25°C:	- %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Sales Information

EAN:	4013902180073
ETIM Class:	EC002328
Custom tariff number:	39269097
Minimum order quantity:	1

Material

Base unit material:	Polypropylene
Cover material:	Polypropylene

Accessories

97911501 - DH 55 - ceiling hook

97911601 - DH 90 - ceiling hook

97911801 - DH 65 - ceiling hook

97924001 - NAS-AL - IBT Accessories

97924201 - NA-AL - IBT Accessories

97924301 - NA-AL/gl - IBT Accessories

Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299