



DC-22A / DC-22B (440V DC) -
DC-23A / DC-23B (220V DC) 200 A / 200 A
AC-20A / AC-20B (690V AC) 250 A / 250 A
SELECTION 3 Rotary switch

Depth	75	-	-
AC-22A / AC-22B (500V AC)	250 A / 250 A	DC Rated operational voltage (Ue)	220 V
DC-23A / DC-23B (500V DC)	200 A / 200 A (2 poles in series for each polarity)	Mechanical life	10.000 cycles
Type	Handle	-	-
DC-21A / DC-21B (220V DC)	250 A / 250 A	Height	108 mm
AC-23A / AC-23B (500V AC)	250 A / 250 A	Rated current	250
Rated current	250	DC-21A / DC-21B (500V DC)	
AC-21A / AC-21B (500V AC)	250 A / 250 A	AC-21A / AC-21B (400V AC)	250 A / 250 A
DC-20A / DC-20B (400V DC)	250 A / 250 A	Power dissipation per pole	5,8 W
-	-	AC-22A / AC-22B (690V AC)	125 A / 160 A
DC-21A / DC-21B (440V DC)	-	Rated tightening torque	20 Nm
Rated short-time withstand current for 1s (Icw)	9 kA	Electrocod	150
Rated insulation voltage (Ui)	800	Description	Rotary switch disconnecter
-	-	Maximum busbar width	32 mm
Rated impulse withstand voltage (Uimp)	8	Pre-arrangement for lock in OFF position	Yes (ø8 mm max)
AC Rated operational voltage (Ue)	400V	Code	MSS 250
DC Maximum operational voltage (Ue max)	500V	DC-20A / DC-20B (220V DC)	250 A / 250 A
Maximum number of auxiliary contacts that can be installed	1	No. of poles	4P
MECHANICAL CHARACTERISTICS	-	AC RATED OPERATIONAL CURRENT (Ie)	-
DC-21A / DC-21B (400V DC)	-	AC-23A / AC-23B (400V AC)	250 A / 250 A
DC-22A / DC-22B (220V DC)	250 A / 250 A	No. of poles	4P
Standard	EN 60947-3	DC-20A / DC-20B (440V DC)	-
SELECTION 1	Command devices	Category	Circuit control
Rated voltage	400	Rated voltage	400
-	-	SELECTION 2	Switch disconnectors
Conditional short-circuit current with fuse (Icc)	50 kA (gG 250A)	DC-23A / DC-23B (440V DC)	-
Weight (kg)	2	Weight (kg)	2
Group	xyz	Width (mm)	230
DC-22A / DC-22B (500V DC)	200 A / 200 A (2 poles in series for each polarity)	AC Maximum operational voltage (Ue max)	690 V
-	-	AC-23A / AC-23B (690V AC)	100 A / 125 A
Rated short-circuit current making capacity (Icm)	30 kA	DC-23A / DC-23B (400V DC)	200 A / 200 A (2 poles in series for each polarity)
AC-22A / AC-22B (400V AC)	250 A / 250 A	DC RATED OPERATIONAL CURRENT (Ie)	-
Minimum cable size	95 mm²	DC-20A / DC-20B (500V DC)	250 A / 250 A
SEO	Disconnecter	DC-22A / DC-22B (400V DC)	-
ELECTRICAL CHARACTERISTICS	-	AC-21A / AC-21B (690V AC)	250 A / 250 A
Maximum cable size (rigid/flexible)	150 / 70 mm²	Rated current	250

DIMENSIONAL





STANDARDS/APPROVALS

