


date: 23/10/2026

SL764+ PL MP S/D

Part number 3115655







IP 40 | CLASS I | DALI | TOUCH | EN

Description

Suspended, LED luminaire for indoor, comprising:

- Extruded aluminium housing, anodised (EV1), die-cast aluminium endcaps, polyester powder coat finish
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
- Streamlined, simple design with flush end caps
- High-quality workmanship of profile connections for a perfect look
- Direct / indirect light distribution
- Through-wiring designed
- Simple and convenient lighting installation
- Interchangeable lighting inserts
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Complete with steel suspension cable (1.5 m), transparent power cable and canopy
- Continuous mounted options and many other configurations are available at www.light-performer.com

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Product data

ETIM Group:	EG000027	**ETIM Class:**	EC001743

General information

Lampholder:	LED	**Light source:**	LED
Luminaire lumen output [lm]:	14140	**Luminaire wattage [W]:**	88 W
Luminous efficacy [lm/W]:	161	**CRI:**	80
Colour temperature [K]:	4000	**Colour / Finishing:**	GR-EV1 / Anodised grey / Matt
IP degree of protection:	IP40	**Impact resistance / impact energy:**	IK05 0.7J xx3
Protection class:	I	**Optic:**	S/D - Symmetric mainly indirect
Beam angle:	2 x 39°/41°	**Net weight [kg]:**	8.226
Overall length [mm]:	2532	**Overall width [mm]:**	44
Overall height [mm]:	66		

Mechanical features

Shape:	Rectangular	**Housing material:**	Aluminium
Diffuser material:	Transparent plastic	**Glow wire test [°C]:**	650 °C

Electrical features

Voltage type:	AC	**Input voltage [V AC]:**	220/240
Input frequency [Hz]:	220-240V 50/60Hz	**Power factor / COS Φ:**	>0.9
Input voltage [V DC]:	186/250	**Inrush current [A/µs]:**	14 / 304
C10 1.5 mm²:	30	**C16 2.5 mm²:**	46
B10 1.5 mm²:	18	**B16 2.5 mm²:**	28

Installation

Application area:	Indoor lighting	**Mounting type:**	Linear systems
Min. ambient temperature [°C]:	10	**Max. ambient temperature [°C]:**	40

Light features


MacAdam:	3	**Lumen maintenance:**	L80B10@50000h
Distribution of light emission:	Direct/Indirect	**DFF - Downward Flux Fraction [%]:**	20
UFF - Upward Flux Fraction [%]:	80	**UGR max.:**	11.0

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Photometric data



To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com