



Main

Product range	Thorsman
Range of product	Thorsman installation material
Product type	Cable tie
Colour	Black
Quantity per package	Set of 100

Complementary

Minimum tightening diameter	3 mm
Maximum tightening diameter	27 mm
Condition of use	Indoor/outdoor
Resistance to tearing	Resistance to tearing: 80 N
Material	PA (polyamide) 6.6 UV-stabilised
Length	120 mm
Width	2.5 mm
Thickness	1.1 mm
Net weight	0.031 kg
Market segment	Small commercial

Environment

Environmental characteristic	Fire resistance needle flame 30 s conforming to IEC 60695-11-5
Flame retardance	Self-extinguishing conforming to UL 94 V2
Ambient air temperature for operation	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.5 cm
Package 1 Width	9.5 cm
Package 1 Length	21 cm
Package 1 Weight	37.2 g
Unit Type of Package 2	BAG
Number of Units in Package 2	100
Package 2 Height	7 cm
Package 2 Width	50 cm
Package 2 Length	70 cm
Package 2 Weight	3.77 kg
Unit Type of Package 3	S35
Number of Units in Package 3	200
Package 3 Height	15 cm

Package 3 Width	40 cm
Package 3 Length	60 cm
Package 3 Weight	8.32 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations