



Hoofd

Range	TeSys
Device short name	LA4D
Product or component type	Onderdrukkingsmodule
Compatibiliteit product	3P LC1D80...D150 4P LC1D80004...D115004 4P LC1D40008...D80008

Complementair

Montagezone	Bovenzijde
Mounting mode	Met schroeven
Ontstoringstechnologie	RC-circuit
Spanning stuurkring	110...240 V AC 50/60 Hz
Maximum piekspanning	3 Uc
Net weight	0,018 kg

Omgeving

Standards	IEC 60947-5-1 EN 60947-5-1 UL 60947-5-1 CSA C22.2 Nr 60947-5-1 GB/T 14048,5
Product certifications	UL[RETURN]CSA
IP beschermingsgraad	IP2x conform aan IEC 60529
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...80 °C

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5,000 cm
Package 1 Width	4,200 cm
Package 1 Length	2,700 cm
Package 1 Weight	22,000 g
Unit Type of Package 2	S01
Number of Units in Package 2	78
Package 2 Height	15,000 cm
Package 2 Width	15,000 cm
Package 2 Length	40,000 cm
Package 2 Weight	1,870 kg
Unit Type of Package 3	P06
Number of Units in Package 3	2496
Package 3 Height	75,000 cm

Package 3 Width	60,000 cm
Package 3 Length	80,000 cm
Package 3 Weight	70,612 kg

Duurzaamheid van het aanbod

Duurzaamheids status van het aanbod	Green Premium product
REACH-regelgeving	 REACH-verklaring
REACH vrij van SVHC	Ja
EU-richtlijn RoHS	Voldoet  EU-verklaring RoHS
Vrij van giftige zware metalen	Ja
Kwikvrij	Ja
RoHS-regulering China	 RoHS-verklaring China
Informatie over RoHS-vrijstelling	 Ja
Milieu Profiel	 Milieuprofiel Van Het Product
Circulair Profiel	Geen specifieke recycling vereist
WEEE	Het product moet op markten van de Europese Unie worden afgevoerd volgens specifieke afvalinzamelingsregels en mag nooit in een gewone vuilnisbak terechtkomen.

contractuele waarborg

Garantie	18 months
----------	-----------