

TERMSERIES-COMPACT PROMO**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Using the all-rounder in a small space

TERMSERIES-compact - universal relay with maximum vibration resistance

- Extremely compact with only 6 mm width and 63 mm depth
- 100 % vibration-proof thanks to enclosed design
- Simplified function check thanks to integrated status LED
- Particularly tamper-proof thanks to permanently installed relays

General ordering data

Version	TERMSERIES-compact, Number of contacts: 1, CO contact AgNi, PUSH IN
Order No.	2899000000
Type	TERMSERIES-COMPACT PROMO
GTIN (EAN)	4064675905660
Qty.	10 pc(s).

TERMSERIES-COMPACT PROMO

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	62.5 mm	Depth (inches)	2.461 inch
Height	89.4 mm	Height (inches)	3.52 inch
Width	6.4 mm	Width (inches)	0.252 inch
Net weight	28.19 g		

Temperatures

Operating temperature	-40 °C...60 °C
-----------------------	----------------

Load side

Contact type	1 CO contact (AgNi)
--------------	---------------------

General data

Colour	black
--------	-------

Connection data

Wire connection method	PUSH IN	Stripping length, rated connection	9 mm
Wire cross-section, solid, min.	0.14 mm ²	Wire cross-section, solid, max.	1.5 mm ²
Wire connection cross section, finely stranded, min.	0.14 mm ²	Wire connection cross section, finely stranded, max.	2.5 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	0.14 mm ²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	1.5 mm ²

Classifications

ETIM 6.0	EC001437	ETIM 7.0	EC001437
ETIM 8.0	EC001437	ETIM 9.0	EC001437
ETIM 10.0	EC001437	ECLASS 9.0	27-37-16-01
ECLASS 9.1	27-37-16-01	ECLASS 10.0	27-37-16-01
ECLASS 11.0	27-37-16-01	ECLASS 12.0	27-37-16-01
ECLASS 13.0	27-37-16-01	ECLASS 14.0	27-37-16-01
ECLASS 15.0	27-37-16-01		

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	7a, 7cl
REACH SVHC	Lead 7439-92-1
SCIP	9e2cbc49-76d9-4611-b8ec-5b4f549a0aa9

Approvals

ROHS	Conform
------	---------

Downloads

Catalogues	Catalogues in PDF-format
------------	--