48512

Standard opening voltage release second MX, MasterPact NW drawout, 48/60VDC, 48VAC





Main

Range	MasterPacT
Range of product	MasterPact NW MasterPact NW DC
Device short name	second MX
Product or component type	Voltage release
Device application	Control
Voltage release type	Second opening coil Instantaneous voltage release
Control type	Standard
[Uc] control circuit voltage	48 V AC 50/60 Hz 4860 V DC
Circuit breaker mounting mode	Drawout
Range compatibility	Masterpact MasterPact NW Masterpact MasterPact NW DC

Complementary

Operating threshold	0.71.1 x Un opening	
Response time	50 ms +/- 10 %	
Supply holding power	4.5 VA	

Packing Units

•		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.5 cm	
Package 1 Width	6.0 cm	
Package 1 Length	8.3 cm	
Package 1 Weight	1.164 kg	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

	<u> </u>	
Warranty	18 months	