


Data sheet

OpDAT VADT splice 4xLC APC OS2, 20.0 m, cable Ø2.3 mm


Page 1/5

P/N
150F049HK0020E
EAN 4251394642888
2025/09/01
Version: G

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- compact fiber optic termination unit for flush mounted outlets or cavity wall boxes
- Box ready for installation, pre-terminated with singlemode indoor cable and equipped with adapters including laser protection for the connection of up to four fiber optic patch cables.
- The second cable end is open to be inserted, pulled in or blown into empty tubes. Suitable for splicing or for mounting field attachable fiber optic connectors (OpDAT FAST® Hybrid).
- cable easy to mount on carton drum
- quick and easy unwinding of the cable without removing the cable drum from the outer box for cable lengths of 10 - 60 m
- Two cable types available:
- Mini Breakout Cable Compact, white, Ø 4.5 mm
- FITH cable, white, Ø 2.3 mm
- single mode fiber OS2, E9/125 µm, bend insensitive according to ITU-T G.657.A2, compatible to ITU-T G.652.D
- supplied with fixing material
- color box pure white (similar to RAL 9010)
- cable lengths: 5 to 100 m in 5 m steps
- (replace XX in the part number by the length, for example 05=5 m, A0=100 m)
- all available variants can be created with the VADT configurator



Data sheet

Page 2/5

OpDAT VADT splice 4xLC APC OS2, 20.0 m, cable Ø2.3 mm

P/N

150F049HK0020E

EAN 4251394642888

2025/09/01

Version: G

Technical Data

General Data	
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	wall outlet
Mounting style	AP
Transmission technology	Fiber optic
Color	white
Dimensions	
Dimension (L x W x H)	85 mm x 100 mm x 35 mm
Dimension (L x W x H)	3.346 in. x 3.937 in. x 1.378 in.
Mode type of the fiber	Singlemode
Fiber class	OS2: IEC 60793-2-50 B6_a, B6_b & ITU-T G.657.A2, G.657.B2, G.652.D
Shape	APC (Angled Physical Contact)
Fiber construction	9/125 µm

Connections/interfaces	
Connector technology interface 1	LC APC
Number of ports interface 1	4
Number of equipped ports interface 1	4
Number of blind	2
Cable sheath diameter (min. - max.)	
Cable sheath diameter	2.3
Cable sheath diameter	0.091
Cable access/outlet	bottom
Connection cable length	20 m
Connection cable length	65.62 ft



Data sheet

Page 3/5

OpDAT VADT splice 4xLC APC OS2, 20.0 m, cable Ø2.3 mm

P/N

150F049HK0020E

EAN 4251394642888

2025/09/01

Version: G

Technical Data

Electrical/ optical properties

Insertion loss	max. 0,3 dB
Return loss	min. 65 dB

Mechanical data

strain relief	aramide fibres
---------------	----------------

Materials and material properties

Material - Housing	Plastics
Material - Coupler housing	Plastics
Material - Sleeve	ceramic, slotted
Material - Ferrule	Ceramic
Flame retardancy	yes
Halogen free	yes

Standards/Regulations

Generic cabling systems

General requirements	ISO/IEC 11801-1
----------------------	-----------------

Lichtwellenleiter: LWL-Innenkabel

Sectional specification for classÂ B single-mode fibres	ISO/IEC 60793-2-50 type B.1.3 & B6_a
---	--------------------------------------

Optical fibers - Interconnecting devices and passive components - basic test and measuring methods

Fibre optic interconnecting devices and passive components - Insertion loss	IEC 61300-3-4
Fibre optic interconnecting devices and passive components - Return loss	IEC 61300-3-6
Fibre optic interconnecting devices and passive components - Visual inspection of plug end face	IEC 61300-3-35

Common test methods for cables under fire conditions

Fire behaviour - class (EN 50399)	B2ca
-----------------------------------	------



Classifications

ETIM 7.0	EC001409
ETIM 8.0	EC001409
ETIM 9.0	EC001409
ETIM 10.0	EC001409



Data sheet

Page 4/5

OpDAT VADT splice 4xLC APC OS2, 20.0 m, cable Ø2.3 mm

P/N

150F049HK0020E

EAN 4251394642888

2025/09/01

Version: G

Technical Data**Packing details**

Type of packaging 1 pc(s) / box

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).



Data sheet

Page 5/5

OpDAT VADT splice 4xLC APC OS2, 20.0 m, cable Ø2.3 mm

P/N

150F049HK0020E

EAN 4251394642888

2025/09/01

Version: G

Illustrations

Dimensional drawing

