

RCL425615T

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Product image

Similar to illustration

General ordering data

| | |
|------------|---|
| Version | , Relay, Number of contacts: 2, CO contact AgNi, Rated control voltage: 115 V AC, Continuous current: 8 A, Plug-in connection |
| Order No. | 2494300000 |
| Type | RCL425615T |
| GTIN (EAN) | 4050118517514 |
| Qty. | 20 items |

RCL425615T

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Dimensions and weights

| | | | |
|------------|---------|-----------------|-------------|
| Depth | 29 mm | Depth (inches) | 1.1417 inch |
| Height | 15.7 mm | Height (inches) | 0.6181 inch |
| Width | 12.7 mm | Width (inches) | 0.5 inch |
| Net weight | 13 g | | |

Temperatures

| | | |
|-----------------------|---------------------|----------------|
| Storage temperature | Ambient temperature | -40 °C...70 °C |
| Operating temperature | | |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

Control side

| | | | |
|-----------------------|----------|------------------|----|
| Rated control voltage | 115 V AC | Status indicator | No |
|-----------------------|----------|------------------|----|

Load side

| | | | |
|-------------------------|---------------------|----------------------------|-------|
| Rated switching voltage | 250 V AC | Max. switching voltage, AC | 132 V |
| Contact type | 2 CO contact (AgNi) | | |

General data

| | |
|--------|-------------|
| Colour | Transparent |
|--------|-------------|

Insulation coordination

| | | | |
|--------------------|---|-------------------|------|
| Pollution severity | 3 | Protection degree | IP67 |
|--------------------|---|-------------------|------|

Connection data

| | |
|------------------------|--------------------|
| Wire connection method | Plug-in connection |
|------------------------|--------------------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC001437 | ETIM 9.0 | EC001437 |
| ETIM 10.0 | EC001437 | ECLASS 14.0 | 27-37-16-01 |
| ECLASS 15.0 | 27-37-16-01 | | |