

PVHXM-M-W+XX06M+11**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The Y cable is used for the parallel connection of several strings in a PV system, e.g. for splitting a line in front of an inverter.

The cables are available in different connection variants.

General ordering data

Version	Photovoltaics, X-Connector Cable, 2x MC4 Male, 1x WM4 C Female, 1x MC4 Female, 6mm ² , 1000 V
Order No.	2814260000
Type	PVHXM-M-W+XX06M+11
GTIN (EAN)	4064675298946
Qty.	1 pc(s).

PVHXM-M-W+XX06M+11**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	117.4 g
------------	---------

PV cable harnessing

PV cable version	Cable side	left
	Number	1
	Cable length	160 mm
	Cable colour	black
	Cable cross section	6 mm ²
	Version of cable end [In-Block]	connector
	Connector version	MC 4
	Type of plug-in contact	male
	Cable side	right
	Number	1
	Cable length	200 mm
	Cable colour	black
	Cable cross section	6 mm ²
	Version of cable end [In-Block]	connector
	Connector version	MC 4
	Type of plug-in contact	male
	Cable side	right
	Number	2
	Cable length	200 mm
	Cable colour	black
	Cable cross section	6 mm ²
	Version of cable end [In-Block]	connector
	Connector version	WM4 C
	Type of plug-in contact	female
	Cable side	right
	Number	3
	Cable length	200 mm
	Cable colour	black
	Cable cross section	6 mm ²
	Version of cable end [In-Block]	connector
	Connector version	MC 4
	Type of plug-in contact	female
Rated DC voltage	1,000 V	
Wire cross-section	6 mm ²	

Electrical characteristics

Rated DC voltage	1,000 V
------------------	---------

Classifications

ETIM 6.0	EC001576	ETIM 7.0	EC001576
ETIM 8.0	EC001576	ETIM 9.0	EC001576
ETIM 10.0	EC001576	ECLASS 9.0	27-06-04-02
ECLASS 9.1	27-06-91-90	ECLASS 10.0	27-06-04-02
ECLASS 11.0	27-06-04-02	ECLASS 12.0	27-06-04-02
ECLASS 13.0	27-06-04-02	ECLASS 14.0	27-06-04-02
ECLASS 15.0	27-06-04-02		

PVHXM-M-W+XX06M+11**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Environmental Product Compliance**

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Approvals

Approvals



Approvals MAMID	https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/
ROHS	Conform

Downloads


Approval/Certificate/Document of Conformity	CE-Declaration_PV_Y-X_Cables
Catalogues	Catalogues in PDF-format

PVHXM-M-W+XX06M+11

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings



PVHXM-M-W+XX06M+11

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

