



Main

Range	ComPact
Range of product	ComPacT NSXm new generation
Device short name	MX
Product or component type	Voltage release
Device application	Control
Voltage release type	Opening coil Shunt trip release
Control type	Standard
[Uc] control circuit voltage	24 V AC 50/60 Hz 24 V DC
Range compatibility	ComPact ComPacT NSXm new generation ComPact ComPacT NSXm PowerPact PowerPact B

Complementary

Operating threshold	0.7 Un opening
Response time	< 50 ms
Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Auxiliary connection terminal	Pre-wired 0...0.8 mm ² (AWG 18)stranded copper
Wire stripping length	8 mm
Cable length	1 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6.1 cm
Package 1 Length	8.3 cm
Package 1 Weight	80 g
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	1.927 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov