

SL764+ RF LV

Part number 3112587



Description

Recessed LED luminaire for indoor, comprising:

- Extruded aluminium profile housing, die-cast aluminium end caps, powder-coated
- Black grid for maximum luminaire efficiency, glare reduction and a high uniformity
- Streamlined, simple design with flush end caps
- High-quality workmanship of profile connections for a perfect look
- Predominantly direct light distribution
- Through-wiring designed
- Simple and convenient lighting installation
- Interchangeable lighting inserts
- DALI dimmable
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Includes recessed mounting kit
- Continuous mounted options and many other configurations are available at www.light-performer.com

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

Product data

ETIM Group:	EG000027	ETIM Class:	EC0028g2
-------------	----------	-------------	----------

General information

Lampholder:	LED	Light source:	LED
Lightsource lumen output [lm]:	4670	Luminaire lumen output [lm]:	3870
Luminaire wattage [W]:	32 W	Luminous efficacy [lm/W]:	121
CRI:	90	Colour temperature [K]:	4000
Colour / Finishing:	BK-RAL9005 / Black RAL9005 / Textured	IP degree of protection:	IP30
IP above/below ceiling:	IP30/IP33	Impact resistance / impact energy:	IK05 0.7J xx3
Protection class:	I	Optic:	S/A - Symmetric direct
Beam angle:	2 x 38°/38°	Net weight [kg]:	7.17
Overall length [mm]:	1428	Overall width [mm]:	60
Overall height [mm]:	95	Minimum installation depth [mm]:	95

Mechanical features

Shape:	Rectangular	Housing material:	Aluminium
Diffuser material:	No diffuser	Glow wire test [°C]:	650 °C

Electrical features

Voltage type:	AC	Input voltage [V AC]:	220/240
Input frequency [Hz]:	220-240V 50/60Hz	Power factor / COS Φ:	0.9
C10 1.5 mm ² :	21	C16 2.5 mm ² :	35
B16 2.5 mm ² :	21	EEL:	A1

Installation


Application area:	Indoor lighting	Mounting type:	Linear systems
Min. ambient temperature [°C]:	10	Max. ambient temperature [°C]:	40

Light features

MacAdam:	3	Lumen maintenance:	L80B10@50000h
Distribution of light emission:	Direct	UGR max.:	18.0

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

Photometric data




Optional accessories


SL764+ RF



3122585
External Casambi module
■ BK-81 / Black



3122586
Single wireless wall switch
□ WH-87 / White



3122587
Double wireless wall switch
□ WH-87 / White

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>