Front part

FT68R



FT68R

Front part

Productnumber: 98206801
Dimensions: 145 x 145 x 27 mm

Front part, for use in combination with IBTLED 1-O installation box in site-cast concrete, protection class IP30, rated insulation voltage: 400V AC, Halogen free

Internal diameter 68 mm, diameter of external aperture edge min. 74 mm, adhesive fixing or nail installation



Created at 04.06.2026. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Type of protection:	IP30
Suitable for:	Concrete construction

Colours

Cover colour:	grey

Dimensions

Width:	145 mm
Length:	145 mm
Height:	27 mm
Weight:	0.069 kg

Material characteristics

Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability:	650 °C (EN 60695-2-11)

mechanical properties

Type of fastening:	adhesive fixing or nail installation
Type of accessory:	Universal front piece

Sales Information

EAN:	4013902607839
ETIM Class:	EC002472
Custom tariff number:	39269097
Minimum order quantity:	1