
Terminal block enclosure

ALR 1010-4²



ALR 1010-4²

Terminal block enclosure

CUSTOMIZABLE

Productnumber: 16040801
Dimensions: 100 x 100 x 81 mm

Terminal block enclosure, protection class IP66, nominal cross-section 4 mm², Ui=400V AC, Aluminium, powder-coated painting, internal fixing points, for installations in industrial environments and protected outdoor areas

equipped with 10-pole terminal block 4mm² (Contaclip BKA 4 type)

IP66 | 4² | IK09 | 400V AC

Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Max. conductor cross section:	4 mm²
Type of protection:	IP66
UL Type Rating:	not specified

Dimensions

Width:	100 mm
Length:	100 mm
Height:	81 mm
Weight:	0.66 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes

mechanical properties

Type of fastening:	Wall/ceiling mounting
Impact strength:	IK09
Sealable:	yes
Fastening:	internal fixing points

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	75 °C
24h ambient temperature:	60 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902120192
ETIM Class:	EC002713
Custom tariff number:	85369095
Minimum order quantity:	1

Material

Base unit material:	Aluminium, powder-coated painting
Cover material:	Aluminium, powder-coated painting
Sealing material:	Polyurethane

Accessories

15400401 - AL ALS-kl - External attachment set

15421001 - AL ASS - External hinge set